Form 3160-5 (November 1983) (Formerly 9-331)	UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other instructions on re- BUREAU OF LAND MANAGEMENT	Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. SF 078566A
	DRY NOTICES AND REPORTS ON WELLS form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTER OR TRIBE NAME
OIL GAS WELL	OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	El Paso Natural Gas Company	8. FARM OR LEASE NAME HOWell

FRACTURE TREAT

REPAIR WELL

SHOOT OR ACIDIZE

		l
OIL GAS WELL OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		8. FARM OR LEASE NAME
El Paso	Natural Gas Company	Howell
3. ADDRESS OF OPERATOR		9. WELL NO.
Post Of	fice Box 4289,Farmington,NM 87499	9 4A
4. LOCATION OF WELL (Report location See also space 17 below.)	clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR WILDCAT
At surface 1690'S.	1780'E	Blanco Mesa Verde
CEIVED		11. SEC., T., R., M., OR BLE. AND Sec. 27, T-28-N, R-8-W N.M.P.M.
14. ERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
1983	6283 GL	San Juan NM
18.00 MANAGEMENT CE AREA CEL A	ppropriate Box To Indicate Nature of Notice, Report	, or Other Data
OF LAN RESOURCE OF INTE	NTION TO:	UBSEQUENT REPORT OF:
MINGTON	PULL OR ALTER CASING	

(Other)

(Note: Report results of multiple completion on Well
Completion or Recompletion Beport and Log form.)

17. UNSCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

7-29-85 TD 3030'. Ran 73 jts. 7", 20.0#, K-55 casing 3018' set @ 3030'. Cemented with 140 sks. Class "B", 65/35 POZ mix, 6% gel, 2% calcium chloride, 1/2 cu ft Perlite/sk (270 cu.ft.)followed by 100 class B, 2% calcium chloride (118 cu ft). WOC 12 hours. Held 1200#/30 minutes. Top of cement @ 1200'.

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

7-31-85 TD 5400'. Ran 50 jts. 4 1/2", 10.5# , K-55 casing liner 2565' set @ 5400'. Float collar set at 5388'. Top of liner set at 2835'. Cmt'd w/50 class B sks,50/50 POZ mix, 2% gel , 0.6% fluid loss additive (62 cu ft), followed by 280 class B, 50/50 POZ mix, 2% gel, 6.25# Gilsonite, 1/4# Flocele, 0.6% fluid loss additive (378 cu ft). WOC 18 hrs.



ALTERING CASING

Casing

Running

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA