

5 BLM 1 File  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

NAME OF OPERATOR

DUGAN PRODUCTION CORP.

ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87499

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface

1850' FNL - 1850' FWL

PERMIT NO.

18. ELEVATIONS (Show whether DF, RT, GR, etc.)

6076' GL; 6088' RKB

5. LEASE DESIGNATION AND SERIAL NO.

NM 37913

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

La Lee Ann

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Gallegos Gallup Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 28, T27N, R13W, NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & Surface Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

M.I. & R.U. Four Corners Drilling Company rig #3. Spudded a 12 1/4" hole at 12:15 PM on 12-10-85. Drilled to 220'. Ran 7 jts. 8-5/8" OD, 24#, 8 Rd, ST&C L.S. casing (T.E. 201.52') set at 214' RKB. Cemented with 135 sx class "B" plus 2% CaCl<sub>2</sub> (total cement slurry 159 cf). Circulated one bbl cement to surface. P.O.B. @ 4:45 PM. Pressure tested BOP and surface casing 600 psi 30 minutes before drilling out - held OK.

I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

12-11-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOC

\*See Instructions on Reverse Side