DEPUTY ON & GAS INSPECTOR

DEC 2 9 1997

Meter Number:95791 Location Name:BOLACK C LS 16 A Location:TN-27 RG-08

SC-33 UL-I

2 - Federal NMOCD Zone:OUTSIDE Hazard Ranking Score:00



.WIG .MOD 1110

RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

Sandstone 10^{-9} to 10^{-13} cm/sec Shale 10^{-12} to 10^{-16} cm/sec Clay 10^{-12} to 10^{-15} cm/sec

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.



FIELD PIT SITE ASSESSMENT FORM

	GENERAL	Meter: 95-791 Location: Bolack C 15 16A Operator #: 0203 Operator Name: ProductionP/L District: Ballard Coordinates: Letter: Section 33 Township: 27 Range: Or								
1	SITE ASSESSMENT	NMOCD Zone: (From NMOCD Maps) Inside Outside (1) Fee (3) Indian Depth to Groundwater Less Than 50 Feet (20 points) Greater Than 100 Ft (0 points) Wellhead Protection Area: Is it less than 1000 ft from wells, springs, or other sources of fresh water extraction?, or; Is it less than 200 ft from a private domestic water source? Horizontal Distance to Surface Water Body Less Than 200 Ft (20 points) (2) Greater Than 1000 Ft (0 points) Greater Than 200 Ft (20 points) (3) Horizontal Distance to Surface Water Body Less Than 200 Ft (20 points) (3) Name of Surface Water Body Carryon (Surface Water Body: Perennial Rivers, Major Wash, Streams, Creeks, Irrigation Canals, Ditches, Lakes, Ponds) Distance to Nearest Ephemeral Stream (1) < 100'(Navajo Pits Only) (2) > 100' TOTAL HAZARD RANKING SCORE:								
REMARKS		Remarks: Redline Book-Outside Vulnerable Zone Tope-Outside Three pits on site, location drip pit has liquid in it: Will close one pit.								
_~~		PUSH IN								

	ORIGINAL PIT LOCATION				
Z	Original Pit : a) Degrees from North 293° Footage from Wellhead $164'$ b) Length : $27'$ Width : $27'$ Depth : $4'$				
ORIGINAL PIT LOCATION	27' 27' Gy, Whead 293°				
	Remarks: Pictures @ 15:08 (1-4, RollZ) Dump Truck				
MARKS					
REMA					
,					
	Completed By:				
•	Signature Date				

FLLD PIT REMEDIATION/CLOSURE FORM

GENERAL	Meter: 95-791 Location: Bolack C LS 16A Coordinates: Letter: I Section 33 Township: 27 Range: 8 Or Latitude Longitude Longitude Date Started: 10-10-94 Run: 67 92							
FIELD OBSERVATIONS	Sample Number(s): \(\sum \) \(\							
CLOSURE	Remediation Method: Excavation							
REMARKS	Remarks: Sandstope 6' 20yd fill							
	Signature of Specialist: Vole Wilder) (SP3181) 03/16/84							



FIELD SERVICES LABORATORY ANALYTICAL REPORT

PIT CLOSURE PROJECT - Soil Samples Outside the GWV Zone

	SAMPLE	IDENTIFICA'	TION		
	Field ID		Lab ID		
SAMPLE NUMBER:	vw 396		946378		
MTR CODE SITE NAME:	95791		N/A		
SAMPLE DATE TIME (Hrs):	10-10-94		1530		
SAMPLED BY:	N/A				
DATE OF TPH EXT. ANAL.:	16-13-94 NIA				
DATE OF BTEX EXT. ANAL.:			N/A		
TYPE DESCRIPTION:	ΛĈ		light_	July Sand	
REMARKS:			, , , , , , , , , , , , , , , , , , , ,		
		RESULTS			
			T		
PARAMETER	RESULT	UNITS		QUALIFIERS	
			DF		V(ml)
TPH (418.1)	59700	MG/KG		C.1/ .	28
HEADSPACE PID	204	PPM			
PERCENT SOLIDS	93.6	%			
		TPH is by EPA Metho	od 418.1		
Narrative:		······································			
DF = Dilution Factor Used					····
Approved By:			Date:	16/23/94	

****************** Test Method for Oil and Grease and Petroleum Hydrocarbons in Water and Soil

Ferkin-Elmer Model 1600 FT-IR Analysis Report ******************



74/10/13 14:19

Sample identification 746378

Initial mass of sample, g

Valume of sample after extraction, miles 2000

Petroleum Sydrocarbons, ppm 19709.020 Net absorbence of hydrocarbons (2970 cm-1) 1.127

