

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 077111

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Storey Gas Com "A" #1

9. API Well No.

30-045-27791

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Incline Reserves, Inc.

3. Address and Telephone No.

1603 SW 37th St., Topeka, KS 66611 913-267-5033

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2260' FNL, 1480' FEL (SWNE)
Sec. 15, T28N, R9W, NMPM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud, Csg Test & Cmt.
Fracture Treatment

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well on 11/01/90 w/Beeman Drlg. Co. Drilled 12-1/4" hole to 255'. Ran 238' new 8-5/8" 20#/ft csg., landed @ 239'. Cement w/200 sx reg. cmt. Circulate cement to surface. Plug Down @ 2:15 PM, 11/02/90. Pressure test csg to 600 psi.

Drilled 7-7/8" hole to TD of 2375' w/Summit Drlg. Ran 2377' new 4-1/2" 10.5#/ft csg., landed @ 2375'. Cement w/400 sx Poz, 130 sx reg. cmt. Circulate cement to surface. Plug down @ 12:00 AM, 11/10/90. Pressure test csg to 3500 psi.

Acidized perforations from 2114' - 2228' w/750 gal 7-1/2% HCl. Frac'd Fruitland Coal down csg w/994,587 cuft N2, 1026 bbls gelled wtr, 10,000# 40/70 sand, 194,000# 20/40 sand. AIR - 65 BPM, AIP - 2000 psi. SIWH - 4 hrs. Flowed well to pit. 11/26/90.

14. I hereby certify that the foregoing is true and correct

Signed J.P. Garrett Title Vice President

Date 12/19/90

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD

Date _____

JAN 18 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

*See instruction on Reverse Side