Ferm 3160-5	Form approved.	
(November 1983) UNITED STATES SUBMIT IN TRIPLICATES	Budget Bureau No. 100 Expires August 31, 198	4_0135
(Formerly 9-331) DEPARTMENT OF THE INTERIOR (Other Instructions on re-	5. LEASE DESIGNATION AND SER	IAL NO
BUREAU OF LAND MANAGEMENT	SF 078390	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir of use "APPLICATION FOR PERMIT " for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIE	IE NAME
OIL CAS OTHER	7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR	8. FARM OR LEASE NAME	
Morgan Richardson Operating Company		
3. ADDRESS OF OPERATOR	Federal 41-11	
P. 0. Box 1915 Farmington, TM 87489		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCA Basin Fruitland C	
1280' FSL, 960' FWL	11. SEC., T., B., M., OR BLE. AND	
•	SURVET OR AREA	
, ,	11, T28N, R8W, NM	PM
14. PERMIT NO. 15 ELEVATIONS (Show whether DF, RT, GR, etc.) 5925 (GR	12. COUNTY OR PARISH 13. ST.	
30-045-28060 5925 GR	San Juan N	M
Check Appropriate Box To Indicate Nature of Notice, Report, or O	· · · · · · · · · · · · · · · · · · ·	
NOTICE OF INTENTION TO	NT REPORT OF:	
TEST WATER SHUT-OFF PRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	REPAIRING WELL	\neg

(Norg: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.).

SHOOTING OR ACIDIZING

(Other) Production Casing Report


RHOOT OR ACIDIZA

REPAIR WELL

(Other)

ABANDON

Pressure tested surface casing and BOP to 1500 psi for 15 min-held OK. 6 1/4" hole to 2600' KB. Ran 60 jts of 4 1/2", 10.5 $\frac{4}{77}$, J-55 casing. Casing landed at 2600' KB. PBD of 2556' KB. Cemented with 200 sx (774 cf) of Class E containing 3% sodium metasilicate and 1/4~%/sk cello flakes. Tailed in with 150 sx (177 cf) of class B containing 2% CaCl and 1/4 #/sk cello flakes. Circulated cement to surface.



		*	
18. I hereby certify that the foregoing is true and corr	ect Agent	Nov. 27, 1990	
(This space for Federal or State office use)	the second secon		
APPROVED BY	_ TITLE	ACCEPTED FOR RECORD	
		JAN 07 1991	
Tive 18 U.S.C. S.	*See Instructions on Reverse Side	FARMINGTON RESOURCE AREA	