

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0100
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Coalbed Methane ☒	5. LEASE DESIGNATION AND SERIAL NO. NM-03198
2. NAME OF OPERATOR McKenzie Methane Corporation	6. IF INDIAN, ALLOTTEE OR TRIBE NAME _____
3. ADDRESS OF OPERATOR 1911 Main Ave., #255, Durango, Colorado 81301	7. UNIT AGREEMENT NAME _____
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1005' FSL, 1225' FWL	8. FARM OR LEASE NAME Frost
14. PERMIT NO.	9. WELL NO. 502
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6541' GL	10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec25-T27N-R10W
	12. COUNTY OR PARISH San Juan
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Drilling Report	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

RECEIVED
BLM

91 JAN 31 PM 1:47

019 FARMINGTON, N.M.

RECEIVED
MAR 0 1991
OIL CON. DIV.
DIST. 3

SEE ATTACHED

18. I hereby certify that the foregoing is true and correct

SIGNED

Ad Sage / CS

TITLE Operations Manager

DATE 1-30-91

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

FEB 21 1991

*See Instructions on Reverse Side
NMOCD

FARMINGTON RESOURCE AREA

BY

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

McKENZIE METHANE CORPORATION
DAILY DRILLING REPORT
Durango Office

12-23-90 Frost #502
 Sec25-T27N-R10W, San Juan Co., NM
 AART: Waiting on drlg rig. DEPTH: 24
 DAILY: MIRU spud unit. Spud 12-1/4" hole @ 11:00 AM
 12/22/90. Drill to 24' & SD. WODR.
 MUD: air Surveys: N/A

1-17-91 Frost #502
 Sec25-T27N-R10W, San Juan Co., NM
 AART: WOC DEPTH: 220'
 DAILY: MIRU 4 States rig #1. Drlg rat hole, mouse
 hole & finish drlg 12-1/4 surf hole. Drlg from 24'-
 220'. TOH. Ran 5 jts 8-5/8, 24#, J55 SIC csg set @
 212.47 KB. RU & cmt csg w/ 200 sx +3% CaCl + 1/4#/sx
 cellophane flakes. PD & holding @ 9:50 PM 1-16-91.
 Circ 15 bbls cmt to surf. WOC.
 MUD: mud Surveys: 220' - 1.

1-18-91 Frost #502
 Sec25-T27N-R10W, San Juan Co., NM
 AART: DRLG DEPTH: 1660'
 DAILY: WOC. NUBOP. PT BOP and csg to 1000#-OK.
 TIH and drill out cmt and formation to 1660'.
 MUD: water SURVEYS: 728'-3/4, 1287'-1

1-19-91 Frost #502
 Sec25-T27N-R10W, San Juan Co., NM
 AART: TOH DEPTH: 2400'
 DAILY: Drlg from 1660' - TD @ 2400'. Circ & cond hole.
 TOH w/ drill pipe. MW: 8.9 Vis: 40
 Surveys: 1880' -1.

-cont.-

MCKENZIE METHANE CORPORATION
DAILY DRILLING REPORT
Durango Office

1-20-91

Frost #502

Sec25-T27N-R10W, San Juan Co., NM

AART: WOC

DEPTH: 2400'

DAILY: Finish TOH. RU Halliburton. First log on bottom
@ 8:00 AM 1-19-91. Ran openhole logs. RD Halliburton.

TIH. LDDP & DC. RU P.T.I. Casers & ran 66 jts of 4-1/2
11.6, K55 LTC csg. landed @ 2399.55, float @ 2372.32KB

RU Dowell & cmt w/ 325 sx 65/35 POZ + 6% gel + 1/4#/sx
cellophane for lead & 125 sx 50/50 POZ + 2% gel +

1/4#/sx cellophane for tail. Cmt preceded by 20 bbl
mud flush. Circ 18 bbl cmt to surf. PD & holding @

6:40 PM 1-19-91. RR @ 6:40 PM. MW: 8.9 Vis:41

Surveys: 2400 - 0.
