Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

CUMBBY NOTICES AND DEDORTS ON WELLS

FORM APPROVED edget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No

NM 04202

	MOTICES					
orm for proj	posals to d	rill or to d	deepen or	reentry	to a diff	erent

Do not use this form Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Oil Gas Well Other Federal 11 #2 9. API Well No. 2. Name of Operator Incline Reserves, Inc. 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 1603 SW 37th St., Topeka, KS 66 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 913-267-5033 66611 Basin Fruitland Coal
1. County or Parish, State 1450' FSL, 2250' FWL (NESW) Sec. 11, T28N, R9W, NMPM San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans ... Notice of Intent Abandonment New Construction Recompletion X Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud, csg. test & cement Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud well on 12/09/90 w/Beeman Drlg. Co. Drilled $12-\frac{1}{4}$ " hole to 260'. Ran 252' new 8-5/8" 20#/ft csg., landed @ 252'. Cement w/240 sx reg. cmt. Circulate cement to surface. Plug Down @ 1:30 AM, 12/10/90. Pressure test csg. to 600 psi. Drilled 7-7/8" hole to TD of 2310' w/Summit Drlg. Ran 2309' new $4-\frac{1}{2}$ " 10/5#/ft csg., landed @ 2307'. Cement w/400 sx Poz, 135 sx reg. cmt. Circulate cement to surface. Plug Down @ 2:00 AM, 12/15/90. Pressure test csg. to 3500 psi. DECEIVE OIL CON. DIV. DIST. 3 14. I hereby certify that the foregoing is true and correct -12/19/90 Vice President J.P. Garrett Title ACCEPTED FOR RECORD Approved by Conditions of approval, if any: JAN 17 1991 Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

*See Instruction on Reverse Side MMOOO