

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

SF 077107 B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

**SUBMIT IN TRIPLICATE**

1. Type of Well

Oil Well  Gas Well  Other

2. Name of Operator

Incline Reserves, Inc.

3. Address and Telephone No.

1603 SW 37th St., Topeka, KS 66611 913-267-5033

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1290' FSL, 1510' FWL (SESW)  
Sec. 15, T28N, R9W, NMPM

8. Well Name and No.

Federal 15 #2

9. API Well No.

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent  
 Subsequent Report  
 Final Abandonment Notice

TYPE OF ACTION

Abandonment  
 Recompletion  
 Plugging Back  
 Casing Repair  
 Altering Casing  
 Other Spud, Csg Test & Cmt.  
 Change of Plans  
 New Construction  
 Non-Routine Fracturing  
 Water Shut-Off  
 Conversion to Injection  
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud well on 12/01/90 w/Beeman Drlg. Co. Drilled 12- $\frac{1}{4}$ " hole to 260'. Ran 251' new 8-5/8" 20#/ft csg., landed @ 252'. Cement w/210 sx reg. cmt. Circulate cement to surface. Plug down @ 12:45 PM, 12/02/90. Pressure test csg to 600 psi.

Drilled 7-7/8" hole to TD of 2380' w/Summit Drlg. Ran 2390' new 4- $\frac{1}{2}$ " 10.5#/ft csg., landed @ 2380'. Cement w/400 sx Poz, 130 sx reg. cmt. Circulate cement to surface. Plug down @ 2:30 AM, 12/07/90. Pressure test csg to 3500 psi.

**RECEIVED**

JAN 28 1991

OIL CON. DIV. I  
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed J.P. Garrett Title Vice President Date 12/19/90

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_  
Conditions of approval, if any:

ACCEPTED FOR RECORD

JAN 18 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

\*See Instruction on Reverse Side