

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

3. Lease Designation and Serial No.
SF079319

6. If Indian, Allottee or Tribe Name
-

7. If Unit or CA, Agreement Designation
-

8. Well Name and No.

Federal 28-8-31 #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan County, NM

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

SG Interests I, Ltd.

3. Address and Telephone No.

P. O. Box 421, Blanco, NM 87412-0421 (505) 325-5599

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1865' FNL & 1555' FEL
Section 31, T28N, R8W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

Notice of Intent

Subsequent Report

Final Abandonment Notice

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

Other

Change of Plans

New Construction

Non-Routine Fracturing

Water Shut-Off

Conversion to Injection

Production Casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

RECEIVED
DEC 28 1992
OIL CON. DIV.
DIST. 3

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Production Casing: TD @ 2795' on 11-25-92.

Hole Size: 7 7/8"

Casing: 67 Jts (2779') 5 1/2", 15.5#, J-55, Casing set @ 2790', Guide Shoe @ 2790', Float Collar @ 2747', Centralizers @ 2770', 2728', 2644', 2560', 2476', 2392', 2308', 2224', 2140', 2056', 1972', & 1888'.

Cement: 275 sx Pacesetter Lite w/12% gel, 5pps Hi-Seal & 1/4 pps Cello-Seal (2.39 Yield/657 cu ft) + 100 sx Class B w/1% CF-14 & 0.4% Thrifty Lite (1.18 Yield/118 cu ft). Circ 11 bbls cement to surface.

Bump Plug w/1200 psi.

Plug Down @ 5:00 PM on 11-26-92.

14. I hereby certify that the foregoing is true and correct

Signed Earnie A. Base

Title Agent (915) 694-6107

Date 12/03/92

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any: