

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
MERIDIAN OIL

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
1795' FSL, 1730' FEL Sec. 26, T-27-N, R-9-W, NMPM

5. Lease Number  
SF-078358

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name  
Huerfanito Unit

8. Well Name & Number  
Huerfanito Unit #79M

9. API Well No.  
30-045-28948

10. Field and Pool  
Blanco MV/Basin Dk

11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

| Type of Submission                                    | Type of Action                              |
|-------------------------------------------------------|---------------------------------------------|
| <input type="checkbox"/> Notice of Intent             | <input type="checkbox"/> Abandonment        |
| <input checked="" type="checkbox"/> Subsequent Report | <input type="checkbox"/> Recompletion       |
| <input type="checkbox"/> Final Abandonment            | <input type="checkbox"/> Plugging Back      |
|                                                       | <input type="checkbox"/> Casing Repair      |
|                                                       | <input type="checkbox"/> Altering Casing    |
|                                                       | <input checked="" type="checkbox"/> Other - |

RECEIVED  
JUN 21 1993  
PH 4:02  
REGISTRATION NM

## 13. Describe Proposed or Completed Operations

06-18-93 TD 6804'. Ran 160 jts 4 1/2", 11.6#, K-55 LT&C csg, 6791' set @ 6804'. Cmt first stage w/340 sx Class "G" 65/35 Poz w/2% calcium chloride and 0.25#/sx flocele (602 cu.ft.), tail w/100 sx Class "G" w/2% calcium chloride (118 cu.ft.), circ 20 bbl to surface. Stage tools @ 1588' 5035'. Cement second stage w/738 sx Class "G" 65/35 Poz w/2% calcium chloride, 6% gel and 0.25#/sx flocele (1306 cu.ft.), tail w/100 sx Class "G" w/2% calcium chloride (115 cu.ft.), circ 25 bbl to surface. Cement third stage w/340 sx Class "G" 65/35 Poz w/6% gel, 2% calcium chloride and 0.25#/sx flocele (602 cu.ft.), tail w/100 sx Class "G" w/2% calcium chloride (115 cu.ft.). Circ 25 bbl cmt to surface. PT 3800 psi, ok.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 6/21/93

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any: \_\_\_\_\_

ACCEPTED FOR RECORD  
Date \_\_\_\_\_

JUN 21 1993

FARMINGTON DISTRICT OFFICE

NMOCD