

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.  
SF-080382-A

6. If Indian, Allottee or Tribe Name  
NAVAJO NATION - NIIP

7. If Unit or CA, Agreement Designation

8. Well Name and No.  
SCHWERTDFEGER "17" #2

9. API Well No.  
30-045-29008

10. Field and Pool, or Exploratory Area  
BASIN FRUITLAND COAL

11. County or Parish, State  
SAN JUAN, NEW MEXICO

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Marathon Oil Company

3. Address and Telephone No.

P.O. Box 552 Midland, Tx. 79702

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SEC. 17, T-27-N, R-11-W  
1605'FSL & 1135'FEL, UNIT 1

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other DRILLING OPERATIONS  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU FOUR CORNERS #1. SPUDDED 12-1/4" HOLE @ 1600 HRS 11-26-93. DRLD TO 363'. RAN 8 JTS 8-5/8" 24# K-55 STC NEW CSG TO 363'. TX PATTERN SHOE @ 362', INSERT @ 321'. MIXED & PUMPED 300 SX CLASS "B" W/ 2% CACL2, 1/4 PPS CELLOFLAKE, WT 15.6; YIELD 1.18. BUMPED PLUG, CIRC'D 25 SX TO PIT. WOC. N/U 11" 3M DUAL RAM BOP'S, CHOKE MANIFOLD & ROT. HEAD. TESTED BLIND RAMS TO 1200#. TH & TESTED PIPE RAMS, CHOKE MANIFOLD & LINES TO 1200#. TAGGED CMT @ 310'. TOTAL WOC TIME 15 HRS. TESTED CSG TO 1000#. RESUMED DRLG FORM. W/ 7-7/8" BIT.

DRLD TO 2090'. R/U SCHLUMBERGER W.L. BOP & PACKOFF. LOGGED WELL AS FOLLOWS: GR/LDT/ML/CAL TD TO SURF. CHG'D RAMS TO 5-1/2" & RAN 48 JTS 5-1/2" 15.5#, K-55 LTC NEW CSG TO 2090'. FLOAT SHOE @ 2088'; FLOAT COLLAR @ 2045'. MIXED & PUMPED 220 SX CLASS "B" LITE W/ 2% CACL2, 1/4 PPS FLOCELE, 3% KCL, WT 12.6, YIELD 1.75. TAILED IN W/ 220 SX CLASS "B" W/ 1% CACL2, .4% HALAD 344, 3% KCL, WT. 15.6, YIELD 1.18. PLUG DOWN @ 0130 HRS 11-29-93. N/D BOP'S. SET 5-1/2" SLIPS. WELDED ON 5-1/2" BELL NIPPLE; SCREWED ON 5-1/2"X 7-1/16" 3M TBG HEAD. REL RIG @ 0330 HRS 11-29-93.

14. I hereby certify that the foregoing is true and correct

Signature M. J. Sullivan Port.B. ARNOLD

Title DRLG. SUPT.

Date 1-04-94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

PTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side

NM/OCD

FARMINGTON DISTRICT OFFICE

BY SM