

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a well or to install a well.

Use "APPLICATION FOR PERMIT - " for such proposals

RECEIVED
JUN 16 1994

070 FARMINGTON, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

OIL CON. DIV.
DIST. 2

D. Tallant

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

(303) 830-5427

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1790' FNL, 1570' FWL

Section

34

Township

28N

Range

8W

5. Lease Designation and Serial No.

SF-078566A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Storey LS #4A

9. API Well No.

30-045-29050

10. Field and Pool, or Exploratory Area

Mesaverde/Basin Dakota

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Set

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 14.750" surface hole on 2/2/94 at 9:45 hrs. Drilled to 408'.

Set 11-3/4" 42# H-40 surface casing at 401'. Cemented with 185 SX CL B, 88 SX Neat. Circulated 10 BBLS to the surface.

Pressure tested casing to 1500 psi. Drilled a 11" hole to a depth of

2443' on 2/7/94. Set 8-5/8" 24#/32# J-55/K-55 Intermediate DV 18/6

casing at 2443'. Cemented with 1st Stg-180 SX CL B, 2nd Stg-285 SX CL B, Tail w/ 100 SX CL B. Circulated 35 BBLS to the surface. Pressure tested casing to 1500 psi.

Drilled a 7.875" hole to a TD depth of 6735' on 2/11/94. Set 5.5", 15.5#, K-55 Production Long string from surf to btm 6735' cemented with 775' SX 50/50 POZ TOC @ 1900'.

Rig released at 0700 hrs. on 2/11/94.

14. I hereby certify that the foregoing is true and correct

Signed

D. Amore

Title

Staff Asst.

Date

6/1/94

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

FARMINGTON DISTRICT OFFICE

• See instructions on Reverse Side