

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

RECEIVED  
BLM

RECEIVED  
FEB 14 1994

070 FARMINGTON, NM

5. Lease Designation and Serial No.

SF-078306A

6. If Indian, Allottee or Tribe Name

7. If Land for CA, Agreement Designation

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Attention:

Amoco Production Company

D. Tallant

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

(303) 830-5427

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1020'FNL

1850'FEL

Section 2

Township

27N

Range

11W

8. Well Name and No.

Bolack Com

#1

9. API Well No.

30-045-29067

10. Field and Pool, or Exploratory Area

Fulcher Kutz Pictured Cliffs ext.

11. County or Parish, State

San Juan

New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud & Set

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 12 250 surface hole on 1/26/94 at 02:45 hrs. Drilled to 273'.

Set 8-5/8" 24# J-55 surface casing at 268'. Cemented with

200 SX CL B Circulated 20 BBLs to the surface.

Pressure tested casing to 1100 psi. Drilled a 7.875" hole to a depth of

2075' on 1/31/94. Set 5.5 15.5# K-55 long string

casing at 2063'. Cemented with 225 SX lead slurry, Tail w/110 SX CL B

Bump the cement plug with water 18 BBLs good cement to surface.

Rig released at 21:45 hrs. on 01/31/94.

14. I hereby certify that the foregoing is true and correct

Signed

*D. Tallant*

Title

Staff Assistant

Date

02-08-1994

(This space for Federal or State office use)

Approved by

Title

ACCEPTED FOR RECORD

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instructions on Reverse Side

NMOOD

BY

FARMINGTON DISTRICT OFFICE

*Sm*