

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

SF-078566

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Storey D #1M

9. API Well No.

3004529247

10. Field and Pool, or Exploratory Area

Basin Dakota/Blanco Mesaverde

11. County or Parish, State

San Juan New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Patty Haefele

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

(303) 830-4988

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1850' FSL 1610' FEL Sec. 26 T 28N R 8W Unit J

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud and set casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU spud rig. Spud a 17.5" conductor hole on 7/12/95 at 13:00 hrs. Drilled to 75'. Set 13.375" 61# K-55 conductor pipe at 75'. Cement with 200 sx Class B. Cement pipe to surface. Rig released 7/12/95.

Drill a 12.25" surface hole on 10/6/95 at 03:00 hrs. Drilled to 2665'. Set 9.625" 36# J-55 surface casing at 2652'. Cemented with 545 sx Class B 50/50 poz, tail with 200 sx Class B. Circulated 23 bbls to surface. Pressure test casing to 1027 psi.

Drilled a 6.25" hole to a depth of 6833' on 10/14/95. Set Dakota long string: 2.875" 6.4# N-80 production casing at 6803 ft. Set Mesaverde short string: 2.875" 6.4 N-80 production casing at 5062 ft. Cemented with 950 sx Class B 50/50 poz. TOC 2200'. Rig released at 04:00 hrs on 10/15/95.

14. I hereby certify that the foregoing is true and correct

Signed

Patty Haefele

Title

Staff Assistant

Date

10-17-1995

(This space for Federal or State office use)

Approved by

Title

ACCEPTED FOR RECORD

Date

Conditions of approval, if any:

OCT 20 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

FARMINGTON DISTRICT OFFICE

* See Instructions on Reverse Side

BY