

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

6. Lease Designation and Serial No.

SF-079232

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Bolack C LS 11A

9. API Well No.

3004529249

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Patty Haeefe

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

(303) 830-4988

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

790' FNL 1120FWL Sec. 28 T 27N R 8W Unit D

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Set Casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU spud rig. Spud a 12.25" conductor hole on 6/12/95 at 0700 hrs. Drilled to 43'. Set 8.625" conductor pipe at 43'. Cement pipe to surface. Rig released 6/12/95.

MIRURT 6/19/95. Drill a 7.875" surface hole on 6/21/95 at 0900 hrs. Drilled to 2412. Set 5.5" 14# CF-50 surface casing at 2401'. Cemented with 340 sx Class B standard. Circulated 22 bbls to surface. Pressure tested casing to 1050 psi.

Drilled a 4.75" hole to a depth of 4700' on 6/24/95. Set 2.875" 6.5# N-80 production casing at 4678 ft. Cemented with 130 sx Class B lead. TOC 2000'. Rig released at 18:00 hrs on 6/24/95.

14. I hereby certify that the foregoing is true and correct

Signed Patty Haeefe Title Staff Assistant Date 06-28-1995

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

ACCEPTED FOR RECORD

JUL 06 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON DISTRICT OFFICE