Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

BUNEAU OF LAND MANAGEMENT	·
SUNDRY NOTICES AND REPORTS ON WELLS	6. Lesse Designation and Serial No.
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.	NM-04208
Use "APPLICATION FOR PERMIT - " for such proposals	6. If Indian, Allottee or Tribe Name
	7. If Unit or CA, Agreement Designation
1. Type of Well Oil See Other	
Weil Well Other 2. Name of Operator Attention:	8. Well Name and No. McCulley LS #2A
Amoco Production Company Gail M. Jefferson, Rm 1295C	B. API Well No.
J. Address and Telephone No.	3004529305
P O. Box 800, Denver, Colorado 80201 (303) 830-6157	10. Field and Pool, or Exploratory Area
4. Location of Well (Factage, Sec., T., R., M., or Survey Description)	Blanco Mesaverde
1545' FNL 895' FWL Sec. 14 T 28N R 9W	11. County or Parish, State
Unit E	San Juan New Mexico
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, RI	PORT, OR OTHER DATA
TYPE OF SUBMISSION . TYPE OF ACTION	
Notice of Injent Abendonment Recompletion	Change of Plans
Plugging Beck	New Construction Non-Routine Fracturing
Subsequent Report Cosing Repair	Weter Shut-Off
Final Abandonment Notice Altering Casing Other Splid & Set Casing	Conversion to Injection Dispose Water
Water Report	t results of multiple completion on Well Completion or n Report and Log form.]
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting	any proposed work . If well is directionally drilled, give
subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.}*	
MIRU Spid rig. Spud an 11" conductor hole on 2/21/96 at 08:00 hrs. Drilled to 139'. Set	
8.625" 24# J-55 Conductor pipe at 139'. Cement with 75 sxs Class Rig released 2/21/96.	B. Cement pipe to surface.
2, 2, 50.	
Drill a 7.875" surface hole on 3/31/96 at 21:00 hours. Drilled to 2,640'. Set 5.500" 14#	
K-55 surface casing at 2628'. Cemented with 300 sxs Class B 50/50 poz, tail with 100 sxs	
Class B. Circulated one barrel to surface. Pressure test casing to 1200 psi.	
Drilled a 4.750" hole to a depth of 5057' on 3/24/96. Set. 2.875" N-80 6.5# production casing	
at 5057'. Cemented with 205 sxs Class B 50/50 poz. Estimated TOC 2552'. Rig released	
at 23:45 hours on 3/24/96.	
14. I hereby cartify the the foregoing is true and correct	
Signed Livelle Afferson Tide Sr. Admin. Staff	Asst. Date 4/30/96
() () () () () () () () () ()	RECORD
A	CCEPTED FOR RECORD
Approved by Title	000
Conditions of approval, if any:	MAY 01 1996
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the Ureted States representations as to any matter within its jurisdiction.	any false, ficticious, or fraudulent any FTCE of
representations as to any matter within its jurisdiction.	FARMINGTON
* See Instrictions on Italiens Side	BY 643