

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT



SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Roddy Production Company

3. Address and Telephone No.

P. O. Box 2221, Farmington, New Mexico, 87499 (505) 325 - 5220

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1605 ' FNL - 1960 ' FEL, Section 20, T27N, R11W, NMPM

G

5. Lease Designation and Serial No.
NM20496

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Yockey No. 5

9. API Well No.
30 - 045 - 29445

10. Field and Pool, or Exploratory Area
Basin Fruitland Coal

11. County or Parish, State
San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☒ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Roddy Production Company proposes to change the casing and cementing program for this well to the following:

Surface casing: Drill 12 1/4 " hole to 200 '. Run 200 ' of 8 5/8 ", 24 ppf, J or K - 55 casing with equivalent float equipment approved in the APD. Cement with 145 sacks (166.75 cf) of Class G with 2 % CaCl and 0.25 pps celloflake. Volume is 100 % excess over the calculated hole volume. Cement will be circulated to surface.

Production casing: Drill 7 7/8 " hole to a Total Depth of 1940 '. Run 4 1/2 ", 10.5 ppf, J or K - 55 casing to Total depth using same float equipment program approved in the APD. Cement: with 480 sacks (604.80 cf) of 50 - 50 Class G Poz with 2 % gel, 10 % salt, and 0.25 pps celloflake followed by 50 sacks (57.50 cf) of Class G with 0.25 pps celloflake. Volume is 50 % excess over calculated hole volume.

14. I hereby certify the foregoing is true and correct

Signed [Signature]

Title Agent

Date April 1, 1997

(This space for Federal or State office use)

Approved by [Signature]
Conditions of approval, if any:

Title _____

Date APR 1 1997