Form 3160-5 (November 1994)

(Instructions on reverse)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT ECEIVED

FORM APPROVED					
Bud	gct	Burcau	No.	1004-0138	
• • •				an and	

Expires November 30	0,	r	Expires	
---------------------	----	---	---------	--

5.	Lease	Serial	No.

SUNDRY NOTICES AND REPORTS ON WELL'S M. Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for light for l				NM 03380 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE -	- Other instructions of	oreverse side TON, NM		7. If Unit or CA/Agreement, Name and/or No.
Oil X Gas Other 2. Name of Operator				** Well-Name and No. Florence 69
Cross Timbers Operating Company 3a. Address 2700 Farmington Ave., Bldg K.		n. Phone No. (include area cade 505/324-1090		2 _{t.} API Well No. 30-1045-29687
4. Location of Well (Footage, Sec., T., R., M., or Survey Description 855' FNL & 1790' FEL, Sec. 19, T27N	ption)	JAN 2	5 1999 M. 1700	Friritland Coal 11. County or Parish, State
12. CHECK APPROPRI	ATE BOX(ES) TO INDI	CATE NATURE OF NOTIC	73)	San Juan NM OROTHER DATA
TYPE OF SUBMISSION		***************************************	OF ACTION	STOTILE DATA
Notice of Intent	Acidize			
X Subsequent Report	Alter Casing Casing Repair	Deepen Fracture Treat New Construction	Reclamation Recomplete	Start/Resume) Water Shut-Off Well Integrity X Other Spud, surf
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporarily Water Dispo	cog, a proa cog.
13. Describe Proposed or Commpleted Operation (clear If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. If testing has been completed. Final Abandonment Nodetermined that the final site is ready for final inspection MI & RU rotary. Spudded well @ 1 23#, J-55 STC casing and set @ 12 Celloflake. Displaced w/4 bbls f final displacement pressure). Fl tested 7" casing to 1000 psig for 12/13/98. RU and ran new 4-1/2", of 35/65 Pozmix/Cl B cement w/6% w/5#/sx Gilsonite & 1/4#/sx Cello w/1550 psig. Float held OK. Cir released rig @ 2:30 a.m., 12/14/9.	notice norizontally, give subsulformed or provide the Bone the operation results in a notices shall be filed only a second of the operation results in a notices shall be filed only a second of the control of the cont	Inc. locations and measured at No. on file with BLM/BIA. wiltiple completion or recomplete and requirements, including the second of the secon	and true vertices Required substition in a new preclamation, hole to 1 sx Cl B cr 12/05/98 v t to surfa 6-1/4" bit 248'. RU flake foll er. P.D.	depths of all pertinent markers and zones. Sequent reports shall be filed within 30 days interval, a Form 3160-4 shall be filed once have been completed, and the operator has 140°. RU and ran 4 jts 7", ant w/2% CaCl and 1/4#/sx w/500 psig (350 psig over ace. WOC 12 hrs. NU BOP & t. Drilled to 2250°, TD, Dowell & cemented w/225 sx lowed w/100 sx Cl B cement @ 12:35 a.m. 12/14/98
14. I hereby certify that the foregoing is true and correct Name (PrintedTyped) Bobby L. Smith		Title Drilling/	lnonations	Facina
Bollow L C. +		Drilling/C	peracions	engineer Con Out
THIS	SPACE FOR FEDER	AL OR STATE OFFICE	USF	OUTHER FOR REMUT
Approved by		Title		RN 2 1999
Conditions of approval, if any, are attached. Approval of certify that the applicant holds legal or equitable title to which would entitle the applicant to conduct operations thereon.	this notice does not warrar those rights in the subject	it or Office		JAN 2 1999
Title 18 U.S.C. Section 1001, makes it a crime for any fraudulent statements or representations as to any matter within	person knowingly and willfits jurisdiction.	ully to make to any department	ont or agency	of the United States any false, fictitious or