UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Sundry Notices	and Reports on	METTS		
. Type of Well GAS			AUG 2000	5.	Lease Number SF-077951 If Indian, All. or Tribe Name Unit Agreement Nam
. Name of Operat	or	2	-OH CON ON	7 3	one national name
RESOUR		S COMPANY	\$ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ 	8.	Well Name & Number
	e No. of Operator Farmington, NM 874	499 (505) 326- 9	700	9.	Graham #1R API Well No.
	·				30-045-30185
	HI, Footage, Sec., FWL, Sec.26, T-27-1		I		Field and Pool Fulcher Kutz PC County and State San Juan Co, NM
2. CHECK APPROPR	LIATE BOX TO INDICA	TE NATURE OF NO	TICE, REPOR	T, OTHER	DATA
Type of Submis			of Action		
X Notice	of Intent	_ Abandonment		ge of Pla	
		_ Recompletion	New	Construct	tion
Subseq		_ Plugging Back		Routine	Fracturing
m4		Casing Repair Altering Casi		er Shut o	
Finai	Abandonment	Altering Casi		rersion c	
	v	_	conv	CIDION C	o injection
	_x	_ Other -	conv	CIBION C	
		Other -			
3. Describe Pr	roposed or Complete	Other -			
3. Describe Pr	coposed or Complete	Other - d Operations pproved casing	and cement	program	
3. Describe Pr It is intend well. The	coposed or Complete ded to change the a e casing and cement	d Operations pproved casing will be altere	and cement	program o	
3. Describe Pr It is intend well. The	coposed or Complete ded to change the a casing and cement Depth Interval	d Operations pproved casing will be altere	and cement ed as follow	program ovs:	
It is intended well. The Hole Size 8 %"	coposed or Complete ded to change the accasing and cement Depth Interval 0 - 120'	d Operations pproved casing will be altere Csq. Size 7"	and cement ed as follow Weigth 20#	program vs: <u>Grade</u> J~55	
3. Describe Pr It is intend well. The	coposed or Complete ded to change the a casing and cement Depth Interval	d Operations pproved casing will be altere Csq. Size 7" 2 7/8"	and cement ed as follow Weigth 20# 6.4#	program ovs:	
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %"	coposed or Complete ded to change the accessing and cement Depth Interval 0 - 120' 0 - 2633'	d Operations pproved casing will be altere Csg. Size 7" 2 7/8"	and cement ed as follow Weigth 20# 6.4#	program vs: <u>Grade</u> J-55 J-55	
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement	coposed or Complete ded to change the appropriate casing and cement Depth Interval 0 - 120' 0 - 2633'	d Operations pproved casing will be altere Csg. Size 7" 2 7/8"	and cement ed as follow Weigth 20# 6.4#	program vs: Grade J-55 J-55	of the subject
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of	coposed or Complete ded to change the a casing and cement Depth Interval 0 - 120' 0 - 2633' casing - cement wit	d Operations pproved casing will be altered Csg. Size 7" 2 7/8" h 46 sx Class	and cement ed as follow Weigth 20# 6.4#	program ws: Grade J-55 J-55 With 1/4#	of the subject
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of	coposed or Complete ded to change the a casing and cement Depth Interval 0 - 120' 0 - 2633' casing - cement with	d Operations pproved casing will be altered Csg. Size 7" 2 7/8" h 46 sx Class of slurry, 200	and cement ed as follow Weigth 20# 6.4#	program ws: Grade J-55 J-55 With 1/4#	of the subject
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" produ	coposed or Complete ded to change the acceptance and cement Depth Interval 0 - 120' 0 - 2633' casing - cement with the chloride (54 cu.ft.) s. Test casing to action casing - Lea	Csq. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class	weigth 20# 6.4# "B" cement to the content of the co	program vs: Grade J-55 J-55 vith 1/4# o circula	of the subject flocele/sx and 3% te to surface).
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" producellophar	coposed or Complete ded to change the action casing and cement Depth Interval 0 - 120' 0 - 2633' casing - cement with the chloride (54 cu.ft.) s. Test casing to action casing - Leader and 10 pps gilso	Csq. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9	weigth 20# 6.4# "B" cement won to be excess to minutes. ss "B" w/3%	program vs: Grade J-55 J-55 vith 1/4# circula sodium m Class "B	of the subject flocele/sx and 3% te to surface). metasilicate, 1/4 pp metasilicate, 1/4 pp
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" producellophar cellophar	coposed or Complete ded to change the acceptance and cement Depth Interval 0 - 120' 0 - 2633' Casing - cement with the chloride (54 cu.ft.) as. Test casing to action casing - Leader and 10 pps gilsone, 5 pps gilsonite	Csq. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9 and 2% calcium	and cement ed as follow Weigth 20# 6.4# "B" cement won to be excess to minutes. ss "B" w/3% 90 sx 50/50 m chloride	program vs: Grade J-55 J-55 with 1/4# o circula sodium m Class "B (885 cu.f	of the subject flocele/sx and 3% te to surface). metasilicate, 1/4 pp " Poz w/2% gel, 1/4 t. of slurry, 100%
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" produ cellophar cellophar excess to	Depth Interval 0 - 120' 0 - 2633' casing - cement with the chloride (54 cu.ft.) 5. Test casing to action casing - Leane and 10 pps gilsonite circulate to surficion currents of circulate to surficion currents of circulate to surficion currents of circulate to surficion casing to circulate to surficion currents of circulate to surficion casing to circulate to surficion casing the circulate circulate casing the casing t	d Operations pproved casing will be altered Csg. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9 and 2% calcium ace). WOC 8 ha	and cement ed as follow Weigth 20# 6.4# "B" cement was been excess to minutes. ES "B" w/3% 90 sx 50/50 m chloride rs. If cement	program ws: Grade J-55 J-55 with 1/4# coircula sodium m Class "B (885 cu.fent does	flocele/sx and 3% te to surface). metasilicate, 1/4 pp metasilicate, 1/4 pt t. of slurry, 100% not circulate to
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" produ cellophar cellophar excess to	coposed or Complete ded to change the acceptance and cement Depth Interval 0 - 120' 0 - 2633' Casing - cement with the chloride (54 cu.ft.) as. Test casing to action casing - Leader and 10 pps gilsone, 5 pps gilsonite	d Operations pproved casing will be altered Csg. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9 and 2% calcium ace). WOC 8 ha	and cement ed as follow Weigth 20# 6.4# "B" cement was been excess to minutes. ES "B" w/3% 90 sx 50/50 m chloride rs. If cement	program ws: Grade J-55 J-55 with 1/4# coircula sodium m Class "B (885 cu.fent does	flocele/sx and 3% te to surface). metasilicate, 1/4 pp metasilicate, 1/4 pt t. of slurry, 100% not circulate to
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" produ cellophar cellophar excess to surface,	coposed or Complete ded to change the act casing and cement Depth Interval 0 - 120' 0 - 2633' casing - cement with chloride (54 cu.ft. s. Test casing to decide and 10 pps gilsone, 5 pps gilsonite of circulate to surface a CBL will be run	d Operations pproved casing will be altered Csg. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9 and 2% calcium ace). WOC 8 had	and cement ed as follow Weigth 20# 6.4# "B" cement won to excess to minutes. ss "B" w/3% 90 sx 50/50 m chloride rs. If cement won to determine the determine to determine the determine to determine the determine to determine the determine t	program ovs: Grade J-55 J-55 with 1/4# o circula sodium m Class "B (885 cu.fent does	flocele/sx and 3% te to surface). metasilicate, 1/4 pp metasilicate, 1/4 pt t. of slurry, 100% not circulate to
It is intended well. The well of the well open to the well of the well open to the wel	Depth Interval 0 - 120' 0 - 2633' casing - cement with the chloride (54 cu.ft.) 5. Test casing to action casing - Leane and 10 pps gilsonite circulate to surficion currents of circulate to surficion currents of circulate to surficion currents of circulate to surficion casing to circulate to surficion currents of circulate to surficion casing to circulate to surficion casing the circulate circulate casing the casing t	d Operations pproved casing will be altered Csg. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9 and 2% calcium ace). WOC 8 had	and cement ed as follow Weigth 20# 6.4# "B" cement won to excess to minutes. ss "B" w/3% 90 sx 50/50 m chloride rs. If cement won to determine the determine to determine the determine to determine the determine to determine the determine t	program ovs: Grade J-55 J-55 with 1/4# o circula sodium m Class "B (885 cu.fent does	flocele/sx and 3% te to surface). metasilicate, 1/4 pp metasilicate, 1/4 pt t. of slurry, 100% not circulate to
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" produ cellophar cellophar excess to surface, 4. I hereby ce	Depth Interval 0 - 120' 0 - 2633' Casing - cement with the casing - cement with the casing - Lean and 10 pps gilsone, 5 pps gilsonite of circulate to surface a CBL will be run	d Operations pproved casing will be altered Csg. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9 and 2% calcium ace). WOC 8 had	weigth 20# 6.4# "B" cement won to see to minutes. ss "B" w/3% 90 sx 50/50 m chloride rs. If cemeion to determine the	program ovs: Grade J-55 J-55 with 1/4# o circula sodium m Class "B (885 cu.fent does rmine TOC	of the subject flocele/sx and 3% te to surface). etasilicate, 1/4 pp Poz w/2% gel, 1/4 t. of slurry, 100% not circulate to
3. Describe Pr It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" producellophar cellophar excess to surface, 4. I hereby ce	coposed or Complete ded to change the are casing and cement Depth Interval 0 - 120' 0 - 2633' Casing - cement with the chloride (54 cu.ft.) 5. Test casing to detect the case and 10 pps gilson the concept of the circulate to surface a CBL will be run extify that the for	d Operations pproved casing will be altered Csq. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9 and 2% calcium ace). WOC 8 his during complet: egoing is true	weigth 20# 6.4# "B" cement won to see to minutes. ss "B" w/3% 90 sx 50/50 m chloride rs. If cemeion to determine the	program ovs: Grade J-55 J-55 with 1/4# o circula sodium m Class "B (885 cu.fent does rmine TOC	of the subject flocele/sx and 3% te to surface). etasilicate, 1/4 pp Poz w/2% gel, 1/4 t. of slurry, 100% not circulate to
It is intend well. The well. The well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" producellophar cellophar excess to surface, I hereby celloped Ammediately and the surface of the surfa	Depth Interval 0 - 120' 0 - 2633' Casing - cement with the casing - cement with the casing - Lean and 10 pps gilsone, 5 pps gilsonite of circulate to surface a CBL will be run	d Operations pproved casing will be altered Csq. Size 7" 2 7/8" h 46 sx Class of slurry, 200 600 psi for 30 d w/263 sx Class nite. Tail w/9 and 2% calcium ace). WOC 8 his during complet: egoing is true	weigth 20# 6.4# "B" cement won to see to minutes. ss "B" w/3% 90 sx 50/50 m chloride rs. If cemeion to determine the	program ovs: Grade J-55 J-55 with 1/4# o circula sodium m Class "B (885 cu.fent does rmine TOC	of the subject flocele/sx and 3% te to surface). etasilicate, 1/4 pp Poz w/2% gel, 1/4 t. of slurry, 100% not circulate to