

DISTRICT I
1625 N. French Dr., Hobbs, NM 87240DISTRICT II
811 South Frist, Artesia, NM 88210DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410DISTRICT IV
2040 South Pacheco, Santa Fe NM 87505

OIL CONSERVATION DIVISION

2040 S. Pacheco
Santa Fe, NM 87505

WELL API NO.	30-045-30195
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil / Gas Lease No.	
7. Lease Name or Unit Agreement Name	BURROUGHS COM B
8. Well No.	4-A
9. Pool Name or Wildcat	BLANCO MESA VERDE
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	6095'

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMI
(FORM C-101) FOR SUCH PROPOSALS.

1. Type of Well:	OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator	FOUR STAR OIL AND GAS COMPANY
3. Address of Operator	3300 N. Butler Ave. Ste 100 Farmington NM 87401
4. Well Location	Unit Letter <u>P</u> : <u>940'</u> Feet From The <u>SOUT</u> Line and <u>660'</u> Feet From The <u>EAST</u> Line Section <u>2</u> Township <u>27N</u> Range <u>R9W</u> NMPM <u>SAN JUAN</u> COUNTY
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	6095'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐
 OTHER: SPUD NOTICE ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPERATION ☐ PLUG AND ABANDONMENT ☐
 CASING TEST AND CEMENT JOB ☐
 OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Four Star Oil and Gas Co. has completed the following in the subject well.

7/25/ 2000 Move in and rig up. Spud well at 10:15 pm, drill 0 to 358'

7/26/2000 Run 8 joints of 8.625- 32#-J-55 LT&C casing. Pump 268 sacks class B cement, circulate 20 bbls cement to surface.

Test casing to 1500 psi.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Arthur D. Archibeque TITLE Eng. AssistantDATE 08/08/2000TYPE OR PRINT NAME Arthur D. ArchibequeTelephone No. 325-4397

(This space for APPROVAL SIGNED BY CHARLIE T. PEREZ, DEPUTY OIL & GAS INSPECTOR, DIST. 3)

APPROVED
BY

TITLE

DATE

AUG - 9 2000

CONDITIONS OF APPROVAL, IF ANY: