

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 077107
Unit Michener

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 17, 1957


Well No. 5-A is located 1090 ft. from N line and 600 ft. from E line of sec. 31
NE Section 31 20N 9W N.M.P.M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco M.V. San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6069 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 4-16-57, Total Depth 4351'.
 Ran 134 joints 7-5/8", 26.40#, J-55 casing (4340')
 set at 4350'. Two stage cementing tool at 2310'. First stage
 50 sacks Regular cement, 50 sacks Pozmix with 4% gel and 1/4"
 Floccle per sack, followed with 50 sacks Heat Cement. Second stage
 75 sacks Regular cement, 75 sacks Pozmix with 4% gel and 1/4"
 Floccle per sack. Held 1000# 30 minutes.
 Top of cement by temperature survey on second stage at 1710'



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company E. Paso Natural Gas Company

Address Box 997

Farmington, New Mexico

By Original Signed EWELL N. WALSH

Title Petroleum Engineer

