Form	9-331a
(Fah	1051\

1			
ı			
i			 
ł	1		
1			
1			 
1			!
-			 
			į
		:	!

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4. Approval expires 12-31-60.
Land Office 046563
NE/4

		EPORTS ON WELLS	
NOTICE OF INTENTION TO DRILL		QUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS.		QUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SH		QUENT REPORT OF ALTERING CASING.	
NOTICE OF INTENTION TO RE-DRILL OR RI		QUENT REPORT OF RE-DRILLING OR REPAIRQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO SHOOT OR ACID NOTICE OF INTENTION TO PULL OR ALTER		EMENTARY WELL HISTORY SATIONS	×
NOTICE OF INTENTION TO ABANDON WELL.	1/10/00	G-ASIGL SUG CISSUOR	
(INDICATE AB	OVE BY CHECK MARK NATURE OF		5
	*********	September 25	9
Kutz Well No. 2 Gov't is located	1600 ft. from $\begin{bmatrix} N \\ S \end{bmatrix}$ lin	e and ft. from $\begin{bmatrix} F_{\mathbf{x}} \\ W \end{bmatrix}$ line of sec	33
SW NE NE 33	28N 10W	N. M. P. M.	
(½ Sec. and Sec. No.) Fulcher Kutz	(Twp.) (Range)	(Meridian) New Mexico	
(Field)	(County or Subdivision	) (State or Territory)	
	DETAILS OF		ement
	DETAILS OF vective sands; show sizes, weights, and all other imports	and lengths of proposed casings; indicate mudding jobs, c ant proposed work)	
Moved in cable to and located bottom and located bottom down and cleaned inch tubing and la	DETAILS OF Victive sands; show sizes, weights, ing points, and all other imports ools, blew down we mat 2000'. Sanda 6 inch casing with lout well to 2000'. anded at 1996'; per		
Moved in cable to and located bottom and located bottom down and cleaned inch tubing and la	DETAILS OF Victive sands; show sizes, weights, ing points, and all other imports ools, blew down we mat 2000'. Sanda 6 inch casing with lout well to 2000'. anded at 1996'; per	and lengths of proposed casings; indicate mudding jobs, cant proposed work)  It, and pulled tubing. Strung in water treated open hole 1975 to 45,000 pounds of sand. Blew (Original T. D. 2074') Ran 1 forations 1980' to 1996', jet	
Moved in cable to and located bottom 2000 feet through down and cleaned inch tubing and is nipples 1706', 17	DETAILS OF Vertive sands; show sizes, weights, ring points, and all other imports tools, blew down were at 2000'. Sanda 6 inch casing with lout well to 2000'. anded at 1996'; per 188', and 1871'. M	the General Ports before operations may be commended.	
Moved in cable to and located bottom 2000 feet through down and cleaned inch tubing and is nipples 1706', 17	DETAILS OF Vertive sands; show sizes, weights, ring points, and all other imports tools, blew down were at 2000'. Sanda 6 inch casing with lout well to 2000'. anded at 1996'; per 188', and 1871'. M	and lengths of proposed casings; indicate mudding jobs, cant proposed work)  li, and pulled tubing. Strung in water treated open hole 1975 to 45,000 pounds of sand. Blew (Original T. D. 2074') Ran i forations 1980' to 1996', jet loved off cable tools.	
Moved in cable to and located bottom 2000 feet through down and cleaned inch tubing and is nipples 1706', 17  I understand that this plan of work must company  King Cil, Inc.	DETAILS OF voice sands; show sizes, weights, ing points, and all other imports ools, blew down we mat 2000'. Sand-6 inch casing with lout well to 2000'. anded at 1996'; per 88', and 1871'. M	the General Ports before operations may be commended.	
Moved in cable to and located bottom 2000 feet through down and cleaned inch tubing and is nipples 1706', 17	DETAILS OF vertive sands; show sizes, weights, wing points, and all other importances, blew down were at 2000'. Sanda is inch casing with lout well to 2000'. anded at 1996'; per 88', and 1871'. Mestreceive approval in writing of the Bidg.	the General Ports before operations may be commended.	