Form 9-331 (May 1963)

3. ADDRESS OF

16.

UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

SUBMIT IN TRIPLICATE*

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

NM

GEOLOGICAL SURVEY		SF 077106
SUNDRY NOTICES AND REPORTS C (Do not use this form for proposals to drill or to deepen or plug bause "APPLICATION FOR PERMIT—" for such pro	ob to a different	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS OTHER	RELEIVED	7. UNIT AGREEMENT NAME
NAME OF OPERATOR		8. FARM OR LEASE NAME
El Paso Natural Gas Company	MAR 3 1972	Lackey B
ADDRESS OF OPERATOR	1 11000	9, WELL NO.
PO Box 990, Farmington, NM 87401 LOCATION OF WELL (Report location clearly and in accordance with any S See also space 17 below.)	OIL CON. COM.	12 (P&A) 10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface	יפוסיים ו	To. Fizeb and Tool, or wilder
990'S, 1850'W		Basin Dakota

Sec. 21, T-28-N, R-9-W **NMPM** 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OF PARISH 13. STATE 6345'GL San Juan

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other) MULTIPLE COMM ABANDON* CHANGE PLANS	PLETE X	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other)	REPAIRING WELL ALTERING CASING ABANDONMENT*
			crore and nog rorm,)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Due to a casing leak and the lack of workover possibility, it is planned to plug and abandon this well in the following manner:

Squeeze 50 sks. cement into Dakota perforations, spot a 15 sk. cement plug on top of retainer set at 6835'. (Top perf. at 6978').

Perforate squeeze holes opposite the Mesa Verde (4234') and Ojo Alamo (1645').

Spot a 75 sks. cement plug opposite the Mesa Verde and Squeeze 50 sks. into formation. Spot a 50 sk. cement plug opposite the Ojo Alamo and squeeze 25 sks. into formation.

Cut off 5 1/2" casing at free point and spot a 50 sk. cement plug on casing stub.

Spot a 15 sk. cement plug at base of surface casing.

Spot a 10 sk. cement surface plug with a Plug & Abandon marker, clean location.

18. I hereby certify that the foregoing is true and correct SIGNED Original Signed F. H. WOOD	TITLE Petroleum Engineer	DATE March 2, 1972
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	RECEIVED
		MAR 2 1972
*	See Instructions on Reverse Side	U. S. GEOLOGICAL SURVEY