) orm	9-331
(May	1963)

16.

## UNITED STATES DEPARTMENT OF THE INTERIOR verse side)

SUBMIT IN TRIPLICATES

Form approved. Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SF 077111

	GEOLOGICAL SURVEY						
SUNDRY	NOTICES	AND	REPORTS	ON	WELLS		

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.


Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME WELL 8. FARM OR LEASE NAME 2. NAME OF OPERATOR Fl Paso Matural Gas Company Lackey 9. WELL NO. 3. ADDRESS OF OPERATOR 6 Farmington, New Mexico 87401 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. 10. FIEED AND TOOLS OR WILDCAT See also space 17 below.) At surface Undes Chacra 1560'N, 1830'E Sec. 34, T-28-N, R-9-W 12. COUNTY OR PARISH | 13. STATE 14. PERMIT NO. 15. ELEVATIONS (Show whether DF. RT. GR. etc.) New Mexico 6803'GL San Juan

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

<b>8</b> 0.	TPEC :	SEPTION TO:		i	SUBSEQUENT	881 001 071	
TIME WALL BOOKSTOPE		PULL OF ALTER CASING	[]		# 758 KH 2022 E	KMAN NG WHILE	[
FRACT FROPEAT	1	MULTIPLE COMPLETE			FRECUERE TREATMENT	ARLEST FOR CARE	: 
SHOOT OR ACIDIZE		ABANDON*		İ	SHOOTING OR ACIDIZING	ABANDON MENT*	
REPAIR WELL		CHANGE PLANS		İ	(Other)	ultiple sempletion on Wel	<u>Ļ</u> _
(Other)					(Note: Report results of m Completion or Recompletion	Report and Log form.)	

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)
  - T.D. 4115'. Ran 137 joints 2 7/8", 6.4#, K-55 production casing, 4105 12-22-73 set at 4115'. Baffle set at 4105'. Cemented with 931 cu.ft. cement. WOC 18 hours. Top of cement at 1100'.
  - Tested casing to 4000#-0K. 4-8-74 PBTD 4105'. Perf'd 3928-38', 3950-60', 4054-70' with 16 shots per zone. Frac'd with 46,000# 20/40 sand and 44, 950 gallons treated water. Dropped 2 set of 16 balls each. Flushed with 1000 gallons water.





8. I hereby certify that the foregoing is true and cor	rect	
SIGNED XI. A. DILLO.	Drilling Clerk	DATE 4-10-74
(This space for Federal or State office use)		<del>-</del>
APPROVED BY	TITLE	DATE