

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, New Mexico
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1460' FSL & 830' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Casing Report ☒

☐
☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
SF-079634
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
McClanahan
9. WELL NO.
17-E
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 24-T28N-R10W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5883' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-17-79 Ran 165 joints (6594') of 5-1/2", 15.50#, K-55 casing set at 6589' Cemented 1st Stage with 130 sacks Class "B" 50/50 Poz, 6% gel and 1/4# gel flake, followed by 50 sacks Class "B" neat with 2% CaCl. Plug down at 6:30 P.M. 12-17-79. Cemented 2nd Stage with 150 sacks Class "B" 50/50 Poz, 6% gel followed by 50 sacks Class "B" neat with 2% CaCl₂. Plug down at 11:30 P.M. 12-17-79. Cemented 3rd Stage with 270 sacks Class "B" 50/50 Poz with 6% gel. Plug down at 4:30 A.M. 12-18-79. WOCT. Circulated Cement.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Prod. Mgr

DATE December 18, 1979

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

DEC 27 '79

FARMINGTON DISTRICT

BY