UNITED STATES DEPARTMENT OF THE INTERIOR

	Form Approved. Budget Bureau No. 42–R/1424
	5. LEASE SF-065546A
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
S	7. UNIT AGREEMENT NAME
rent	8. FARM OR LEASE NAME
	Newman "B" 9. WELL NO.
	6-E 10. FIELD OR WILDCAT NAME
	Basin Dakota
01 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 19-T28N-R10W
	12. COUNTY OR PARISH 13. STATE
	San Juan New Mexico
CE,	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	5900' GR
	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
state is di tinen	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and t to this work.)*
ints ted	00 P. M. 1-7-80 and drilled to (205') of 8-5/8", 24#, K-55 with 140 sacks of Class "B"
ack	and 3% CaCl. Plug down at ated to surface.
	MAN 1 7 1980
	II I IAN I (1500

GEOLOGICAL	SURVEY	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME
SUNDRY NOTICES AND		7. UNIT AGREEMENT N	AME
(Do not use this form for proposals to drill or reservoir. Use Form 9-331-C for such propos	als.)	8. FARM OR LEASE NAM	IE
1. oil gas ry		Newman "B"	
well gas X other		9. WELL NO.	-
2. NAME OF OPERATOR		6-E	÷
Southland Royalty Compan	у	10. FIELD OR WILDCAT N	IAME
3. ADDRESS OF OPERATOR		<u>Basin Dakota</u>	
P.O. Drawer 570, Farming	ton, New Mexico 87401	11. SEC., T., R., M., OR E	ILK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LO	CATION CLEARLY. See space 17	AREA Section 19-T28	N-R1OW
below.) AT SURFACE: 800' FNL & 1	850' FWL	12. COUNTY OR PARISH	
AT TOP PROD. INTERVAL:		San Juan	New Mexico
AT TOTAL DEPTH:		14. API NO.	NOW TIOX TOO
6. CHECK APPROPRIATE BOX TO	INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW	DF, KDB, AND WD)
·		5900' GR	
REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	H .		
FRACTURE TREAT	H		
REPAIR WELL		(NOTE: Report results of mu	
PULL OR ALTER CASING		change on Form 9-	330.)
MULTIPLE COMPLETE	H		
ABANDON*	. 6		
(other) Spud & Casing Repo	ort X		•
Total Depth casing and neat with 1	1/4" surface hole at 5 of 225'. Ran 5 joints set at 218'. Cemented /4# gel flake per sack 1-7-80. Cement circu	s (205') of 8-5/8" with 140 sacks of and 3% CaCl. Plug	, 24#, K-55 Class "B"
Subsurface Safety Valve: Manu. and Ty	/pe	Set	
18. I hereby certify that the foregoing	is true and correct	•	
SIGINED /m /ya	TITLE Dist. Prod. M	gr. DATE January (3, 1980
	(This space for Federal or State off	ice use)	
ADDOOMED BY	TITLE	DATE	
APPROVED BY	11166	.,	ומפכים בפים חסדם:
	NMOCC'	ACCI	TIEU Ion Rubydi
	*See Instructions on Reverse S	Side	JAN 15'80

*See Instructions on Reverse Side

FARMINGTON DISTRICT BA