

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

PO Drawer 570, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 800' FNL & 1850' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Casing Report

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

SF-065546A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Newman "B"

9. WELL NO.

6-E

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 19, T28N, R10W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5900' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-16-80 Ran 207 joints (6559.15') of 4-1/2", 10.5#, K-55 casing set at 6558'. Cemented 1ST STAGE with 208 sacks of Class "B" 50/50 Poz with 6% gel, 1/4# flocele per sack followed by 50 sacks of Class "B" with 2% CaCl. Plug down at 2:45 A.M. 1-17-80.
1-17-80 Cemented 2ND STAGE with 272 sacks of Class "B" 50/50 Poz with 6% gel followed by 50 sacks of Class "B" with 2% CaCl2. Plug down at 7:00 AM 1-17-80. Cemented 3RD STAGE with 206 sacks of Class "B" 50/50 Poz with 6% gel. Plug down at 10:15 A.M. 1-17-80. Top of Cement at 900'.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Prod. Mgr

DATE January 18, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JAN 23 '80

