

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
SUPRON ENERGY CORPORATION  
3. ADDRESS OF OPERATOR  
P.O. Box 808, Farmington, New Mexico 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1' below.)  
AT SURFACE: 970 ft./S ; 940 ft./W line  
AT TOP PROD. INTERVAL: Same as above  
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☐  
(other) Ran 2-7/8" tubing

5. LEASE  
SF 080724-A  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Zachry  
9. WELL NO.  
25  
10. FIELD OR WILDCAT NAME  
Bloomfield Chacra Extension  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 11, T-28N, R-10W, N.M.P.M.  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5665 R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Drilled 6-3/4" hole w/mud to total depth of 3130 ft. R.K.B. Total depth was reached on 12-19-80.
2. Ran 99 jts. of 2-7/8", E.U.E., 6.50# casing & set @ 3106 ft. R.K.B. w/float collar @ 3075 ft. R.K.B.
3. Cemented w/330 sx of 65-35-6 w/12 1/2# of gilsonite /sk & 200 sx of 50-50 POZ mix w/1/2 lb. of cello flakes/sk. Plug down @ 9:00 p.m. 12-20-80.
4. Ran temperature survey and found cement top at 500 ft.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE December 22, 1980  
Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JAN 08 1981

\*See Instructions on Reverse Side

BY FARMINGTON DISTRICT

