STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

Location of Well: P312810 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:MARTIN GC B 1E Meter #:94381 RTU:1-030-05 County:SAN JUAN

Me'	ter #:94381	Kı	0:1-030 03	_		
	NAME RESEL	RVOIR OR POOL	J	TYPE PROD	METHOD PRO	
UPR	MARTIN GC	B 1E PC 94382		GAS	FLOW	TBG
COMP	(Mortin GC)	41 PC)	1-31-5			
-	\	B 1E DK 94381		GAS	FLOW	TBG
LWR COMP	MARTIN GC	B 1E DK 34301	- 1-30-5			
		PRE-FI	LOW SHUT-IN	PRESSURE DA	ΥTA	
	Hour/Date	Shut-In Le	ength of Tim	e Shut-In	SI Press.	PSIG Stabilzed
	nour/ bace					
UPR COMP	09/27/93	10:30 AM			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
LWR	09/27/93				in a second	Maria de Co
COMP		10:30 AM				uist. E.
		1	FLOW TEST	DATE NO.1	1	
Comme	enced at (ho	our,date)*			Zone P	Producing (Upr/Lwr
COmme			Dr.	RESSURE	Prod	
(ho	TIME our, date)	LAPSED TIM SINCE*	Upper	Lower	I I	REMARKS
	09/27/93	Day 1		190		Both Zones SI
	09/28/93	Day 2	107/10			Both Zones SI
	09/29/93	Day 3	111/11	1 215	-	Both Zones SI
	09/30/93	Day 4		221		DK. DN 9:30
	09/0/193	Day 5	111/11	7 /26		
	10/02/93	Day 6		8 133	·	
Prod	uction rate	during test	ON 930	DDI a in	Hre	Grav GOR
oil:		BOPD bas	sed on	theu (Orif:	ice or Mete	GravGOR
Gas:		MII	O-TEST SHUT-	IN PRESSURI		
	Hour, Dat	e SI Lengtl	n of Time SI	SI Pres	s. PSIG S	tabilized (yes/no)
UPR COME						1
LWR						
COME	P					
			(Continue or	reverse s	ide)	

REMARKS

FLOW TEST NO. 2

PRESSURE

1 1

Zone producing (Upper or Lower):

PROD. ZONE

			Completion	I EMP.	

•					

roduction rate di	uring test				
il:	BOP	D based on	Bbls. in	Hours	Grav GOR
					:
			ed is true and con	nplete to the best	of my knowledge.
pproved	Conservation D	ivision	19O	perator	Amoro Production Con
THE MINISTRE OF					
			Ву	Ju	san Woods
			Ti	de Lill	san Woods I Technologist
sy	· Pile o	CECN, DIST. (63	Ti	tle <u>Jill</u> ate	d Sechnologist

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) ##

LAPSED TIME

BINCE **

TIME

(hour, date)

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).