weil \square

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

other

| | Budget Bureau No. 42-R1424 | | |
|---|---|--|--|
| | 5. LEASE | | |
| | SF-079634 | | |
| | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | | |
| _ | | | |
| | 7. UNIT AGREEMENT NAME | | |
| t | | | |
| | 8. FARM OR LEASE NAME | | |
| | <u> McClanahan</u> | | |
| | 9. WELL NO. | | |
| | #22 | | |
| | 10. FIELD OR WILDCAT NAME | | |
| | Otero Chacra | | |
| | 11. SEC., T., R., M., OR BLK. AND SURVEY OF | | |
| _ | AREA C | | |
| | Section 14, T28N, R17W | | |
| | 12. COUNTY OR PARISH 13. STATE | | |
| | San Juan New Mexico | | |

2. NAME OF OPERATOR

Southland Royalty Company
3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1635' FNL & 1640' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD) 5635 GL

14. API NO.

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Casing Report

gas

well

X

SUBSEQUENT REPORT OF:

change on Form 9-330.)

(NOTE: Report results of multiple completion or zone

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-26-83 Drilled 6-3/4" hole to a total depth of 3000'. Ran 95 joints (2971') of 2-7/8", 6.4#, J55 casing set at 2982'. Cemented first stage with 708 cubic feet of Class "B" containing 50/50 POZ, 6% gel, and 1/4# flocele. Tail in with 77 cubic feet of Class "b" plus 2% CaCl2. Plug down at 4:30 am on 5-26-83. Cement circulated to surface.

| Subsurface Safety Valve: Man | Set @ | Ft. | |
|----------------------------------|--|-------------------|--|
| 18. I hereby certify that the fo | regoing is true and correct Why TITLE Secretary | DATE May 29, 1983 | |
| | (This space for Federal or State office | ce use) | |
| APPROVED BY | TITLE | DATE | |

*See Instructions on Reverse Side



JUN 0 1983