

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☒	DRY ☐											
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. ENVIR. ☐	Other ☐								
2. NAME OF OPERATOR El Paso Natural Gas Company															
3. ADDRESS OF OPERATOR P. O. Box 4289, Farmington, NM 87499															
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 1690'N 1600'W At top prod. interval reported below At total depth															
14. PERMIT NO.				DATE ISSUED SEP 06 1985											
15. DATE SPUDDED 6-21-85															
16. DATE T.D. REACHED 7-1-85															
17. DATE COMPL. (Ready to prod.) 8-23-85															
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6828' GL															
19. ELEV. CASINGHEAD 6828'															
20. TOTAL DEPTH, MD & TVD 5828'		21. PLUG, BACK T.D., MD & TVD 5813'		22. IF MULTIPLE COMPL., HOW MANY* One		23. INTERVALS DRILLED BY Rotary									
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 5327-5782' (Blanco Mesa Verde)						25. WAS DIRECTIONAL SURVEY MADE No									
26. TYPE ELECTRIC AND OTHER LOGS RUN Temp Survey; Densilog NGRL; Ind. Electrolog GR; Prolog Field Analysis; Ind. GR						27. WAS WELL CORED No									
28. CASING RECORD (Report all strings set in well)															
CASINO SIZE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED					
9 5/8"		32.3#		310'		12 1/4"		189 cu ft							
7"		4.7#		3250'		8 3/4"		456 cu ft							
29. LINER RECORD								30. TUBING RECORD							
SIZE		TOP (MD)		BOTTOM (MD)		SACKS CEMENT*		SCREEN (MD)		SIZE		DEPTH SET (MD)		PACKER SET (MD)	
4 1/2"		3096'		5828'		466 cu ft				2 3/8"		5760'			
31. PERFORATION RECORD (Interval, size and number) 5540, 5545, 5571, 5584, 5629, 5637, 5644, 5648, 5746, 5750, 5782 w/1 SPZ. 5327, 5330, 5333, 5339, 5352, 5355, 5358, 5361, 5364, 5375, 5378, 5381, 5384, 5387, 5393, 5396, 5399, 5402, 5405, 5408, 5422, 5440, 5452, 5468, 5484, 5506 w/1 SPZ.								32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.							
								DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED					
								5540-5782		34,000# 20/40 sand&60,694 gals wt					
								5327-5506		87,000# 20/40 sand&115,312 gals wt					
33. PRODUCTION															
DATE FIRST PRODUCTION 8-2-85		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing						WELL STATUS (Producing or shut-in) Shut in							
DATE OF TEST 8-23-85		HOURS TESTED 3 Hrs.		CHOKE SIZE 3/4"		PROD'N. FOR TEST PERIOD →		OIL—BBL. 0		GAS—MCF. 284 MCF		WATER—BBL. 0		GAS-OIL RATIO 0	
FLOW. TUBING PRESS. SI 561		CASING PRESSURE SI 707		CALCULATED 24-HOUR RATE →		OIL—BBL. 0		GAS—MCF. 1861		WATER—BBL. 0		OIL GRAVITY-API (CORR.) 0			
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Shut in to be Sold										TEST WITNESSED BY Don Norton					
35. LIST OF ATTACHMENTS Temp Survey										ACCEPTED FOR RECORD					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records															
SIGNED [Signature]				TITLE Drilling Clerk				DATE 8-29-85							

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMCC

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2010'	2135'	ss. White cr-grn s.	Ojo Alamo	2010'	
Kirtland	2135'	2720'	Gry sh interbedded w/tight gry fine-grn ss.	Kirtland	2135'	
Fruitland	2720'	3040'	Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.	Fruitland	2720'	
Pictured Cliffs	3040'	3990'	Gry, fine-grn tight, varicolored soft ss.	Pic. Cliffs	3040'	
Chacra	3990'	4696'	Gry fn grn silty, glauconitic sd stone w/drak gry shale	Chacra	3990'	
Mesa Verde	4696'	4747'	Gry, fine-grn, dense sil ss., carb sh & coal	Mesa Verde	4696'	
Menefee	4747'	5324'	Gry, fine-grn s, carb sh & coal	Menefee	4747'	
Point Lookout	5324'	5828'	Gry, very fine sil ss w/frequent sh breaks	Pt Lookout	5324'	