STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

| B-32-28.9 | Location of Well: B322809 | Page 1 | A1-R33

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator:	AMOCO	PRODUCTION	COMPANY	Lease/Well	#:DAUM L	3 006E	\$
Meter			RTU:0-00		County	y:SAN	JUAN

Me	ter #:95766		RTU:	:0-000-00	[*] C	oun'	ty:SAN	JUAN	- -	
	NAME RESE	RVOIR OR I	POOL		TYPE PROD	ME'	THOD PRO	OD M	EDIUM PROD	
JPR COMP	DAUM LS 00	GAS	FLOW			TBG				
WR COMP	DAUM LS 00	6E DK 95'	763		GAS		FLOW		TBG	
	\	PRI	E-FLOV	N SHUT-IN	PRESSURE DA	ΥA				
	Hour/Date	Shut-In	Leng	gth of Tim	e Shut-In	SI	Press.	PSIG	Stabilzed	
PR OMP	06/10/96			72		246		6	yes	
WR COMP	06/10/96			72		297		,	gen	
	.		ł	FLOW TEST	DATE NO.1	l			1	
omme	nced at (ho	our,date)*					Zone P	roduci	ng (Upr/Lwr)	
(hc	TIME our, date)	LAPSED SINCE		PR Upper	ESSURE Lower		Prod Temp.	R	EMARKS	
O	06/18/96 Day 1		1	manual 198	336			Bot	Both Zones SI	
C	06/11/96 Day 2		2	216	341		Bot		h Zones SI	
C	13/196	Day	3	239	370			Bot	h Zones SI	
C	14/23/96	Day	4	246	297			Jum C	ower Zone or	
0	15	Day	5	289	247	7		lower	lower z	
	06/25/96	Day	6	305	241	/			,, 0	
Produ Dil:_ Gas:	iction rate	BOPD	based MFCP	on D:Tested t	•	ce c	or Merei	Gra	tv GOR CR	
UPR COMP	Hour, Date	e SI Len	ngth c	of Time SI	SI Press	. PS	į.		ed (yes/no)	
LWR COMP			(Cc	ontinue on	reverse si	de)		JUL 0 1 T. (20)	1996 B N. DUV.	
			(00			,	(90	Dist		

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

FLOW TEST NO. 2

			Total bearing (opper or Count)				
TIME frow, date)	LAPSED TIME	PRES Upper Completion	PRESSURE Upper Completion Lower Completion		REMARKS		
	 			TOUP.			
				ĺ			
		 			· !	 	
· · · · · · · · · · · · · · · · · · ·						_•	
						······································	
	 						
	İ		ł				
duction rate d	luciae esse						
					Grav r):		
				,	,,		
H41K3:							
·			·				
ereby cerrify :	hat the informer	ion herein					
					st of my knowledge.		
proved	JUL 0	3 1996	19	Operator	moco (roo	<u>I </u>	
New Mexico C	Dil Conservation	Division .		<u> </u>	Poullus		
	Johning &	Polingon		By	YORCOME		
	Donuth Cit o	Gas Inspector	-	Title	eld tech		
de	Deputy Oil 8	Gas Inspector			6/27/96		
- 				Date	17777		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage sext shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order sutherizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packet or the tubing have been directbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

unced at flour, date| ++

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 5. The packer leakage test shall commence when both zones of the dual completion are shut-in for previous subilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Plow Ten No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shart-in. Such test shall be continued for seven days in the case of a gas well and for 14 hours in the case of an oil well. Note: if, on an initial packer leakage tent, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Ten'No. 2 shall be conducted even though no leak was indicated during Flow Ten No. 1. Procedure for Flow Ten No. 2 is to be the same as for Flow Ten No. 1 except

- that the previously produced 2000 shall remain shut-in while the 2000 which was previously shut-in is produced.
- 7. Pressures for gas-some tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fafteen-minute intervals during the first hour thereof, and at houtly intervals thereafter, including one pressure measurement immediately priot to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressure may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil some texu: all pressures, throughout the entire text, shall be coordinateably measured and recorded with recording pressure gauges the accuracy of which smart be checked at least review, once at the beginning and once at the end of each text, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only; with deadweight pressures at required above being taken on the gas soos.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Asset Dutart Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing a temperatures (gas soots only) and gravity and GOR (oil zones only).