


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe, N. Mexico

Lease No. _____

Unit NM 020501

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Surface Casing

RECEIVED
SEP 14 1960
U. S. GEOLOGICAL SURVEY
SANTA FE, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 7, 1960

Ohio Government

Well No. 2-26 is located 1850 ft. from N line and 990 ft. from EX line of sec. 26

NE SW NW Sec. 26 28N 11W
(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)


Kutz Canyon San Juan County New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ground ~~surface~~ above sea level is 5569.6 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 8-30-60. Ran 10 jts. 10-3/4" 40# 10-V thd. J-55 and 1 jt. 10-3/4" 32.75# 8rd. H-40 casing set from 8' to 251.16' cemented with 200 sacks regular cement with 3% CaCl₂. Plug down at 2:50 PM 8-31-60. Good cement returns to surface. WOC. Tested casing with 1000# for 30 mins. Tested OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE OHIO OIL COMPANY

Address P. O. Box 120

Casper, Wyoming

By [Signature]

Title Division Production Supt.

