
Form 9-331 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa	ř•
Lease No.	777968	
He	. c. x	معاد (حنة

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	1 1
NOTICE OF INTENTION TO TEST WATER SHUT-OI	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASI	
NOTICE OF INTENTION TO ABANDON WELL	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	Y CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
USA C. J. Holder	Farmington, New Mexico Pebruary 19, 19
ell No. 1 is located 🤧	ft. from S line and S ft. from E line of sec. 21
SE/4 of Section 21 T-	-26-N R-13- W M.N.P.M.
(% Sec. and Sec. No.) (Tr	wp.) (Range) (Meridian)
Underignated Dekota (Field)	(County or Subdivision) (State or Territory)
ate names of and expected depths to objective s	ands; show sizes, weights, and lengths of proposed casings; indicate mudding inha-
ing pe	oints, and all other important proposed work)
USA C. J. Helder Well Ho.	l was gradded on February 15, 1958, and on February
USA C. J. Helder Well Ho. 1 16, 1958, 8-5/8" easing was	l was specied on February 15, 1958, and on Februar s set at 495' with 400 sacks of cement. After wai
USA C. J. Holder Well Ho. 1 16, 1958, 8-5/8" easing was on econt for 24 hours, car	l was specied on February 15, 1958, and on Februar s set at 495' with 400 seeks of cement. After uni sing and water shut-eff were tested with 500 pound
USA C. J. Holder Well Ho. 1 16, 1958, 8-5/8" casing was on comest for 24 hours, cas	l was spudded on February 15, 1958, and on Februar s set at 495° with 460 sacks of cement. After uni
USA C. J. Holder Well Ho. 1 16, 1958, 8-5/8" easing was on sement for 24 hours, on	l was specied on February 15, 1958, and on Februar s set at 495' with 400 seeks of cement. After uni sing and water shut-eff were tested with 500 pound
USA C. J. Holder Well Ho. 1 16, 1958, 8-5/8" easing was on comest for 24 hours, car	l was specied on February 15, 1958, and on Februar s set at 495' with 400 seeks of cement. After uni sing and water shut-eff were tested with 500 pound
USA C. J. Holder Well Ho. 1 16, 1958, 8-5/8" casing was on comest for 24 hours, cas	l was specied on February 15, 1958, and on Februar s set at 495' with 400 seeks of cement. After uni sing and water shut-eff were tested with 500 pound
USA C. J. Holder Well Ho. 1 16, 1958, 8-5/8" easing was on econt for 24 hours, car	l was specied on February 15, 1958, and on Februar s set at 495' with 400 seeks of cement. After uni sing and water shut-eff were tested with 500 pound
USA C. J. Holder Well Ho. 1 16, 1998, 8-5/8" easing was on ecount for 24 hours, car	I was spudded on February 15, 1958, and on February 15 and an February 15 and and an February 15 and an Indian and Indian
USA C. J. Holder Well Ho. 1 16, 1998, 8-5/8" easing was on eccent for 24 hours, car	l was specied on February 15, 1958, and on Februar s set at 495' with 400 seeks of cement. After uni sing and water shut-eff were tested with 500 pound
USA C. J. Holder Well Ho. 1 16, 1998, 8-5/8" easing was on eccent for 24 hours, car	I was spudded on February 15, 1958, and on February 15 and an February 15 and and an February 15 and an Indian and Indian
USA C. J. Holder Well Ho. 1 16, 1958, 8-5/8" easing was on eccent for 24 hours, cas pressure for thirty minutes	l was speeded on February 15, 1958, and on February 15 and an on February 15, 1958, and on February 15 and an
USA C. J. Helder well Ho. 14, 1958, 8-5/8" easing was on econot for 24 hours, car pressure for thirty missates	I was specified on February 15, 1958, and on February 15 and on February 15, 1958, and on February 15 and an enter shat-eff were tested with 500 pounds which held with no drop in pressure. FER 21 1958 OIL CON. COM. OIL CON. 3 The same of the control of the
USA C. J. Helder well Ho. 16, 1958, 8-5/8" easing was on econot for 24 hours, car pressure for thirty minutes of the control o	I was specified on February 15, 1958, and on February 15 and on February 15, 1958, and on February 15 and an enter shat-eff were tested with 500 pounds which held with no drop in pressure. FER 21 1958 OIL CON. COM. OIL CON. 3 The same of the control of the
USA C. J. Helder well Ho. 14, 1958, 8-5/8" easing was on common for 24 hours, car pressure for thirty missates pressure for thirty missates ompany Pan American Petrola	I was specified on February 15, 1958, and on February 15 and on February 15, 1958, and on February 15 and an intermediate of count. After uniting and water shut-off were tested with 500 pounds which held with no drop in pressure. OIL CON 3 Ve approval in writing by the Geological Survey before operations may be commenced.
USA C. J. Holder well Ho. 16, 1958, 8-5/8" easing was on sement for 24 hours, can pressure for thirty minutes ompany Pan American Petrole ddress Box 487	I was specified on February 15, 1958, and on February 15 and on February 15, 1958, and on February 15 and all 495 with 460 sacks of count. After uniting and water shut-eff were tested with 500 pounds which held with no drop in pressures. FEB 21 1958 OIL CON 32 ORIGINAL 324 ORIGINAL 324 ORIGINAL 324
USA C. J. Helder well Ho. 14, 1958, 8-5/8" easing was on common for 24 hours, car pressure for thirty missates pressure for thirty missates ompany Pan American Petrola	I was specified on February 15, 1958, and on February 15 and the South of Commit. After was sing and water shut-off were tested with 500 pounds which held with no drop in pressure. Ve approval in writing by the Geological Survey before operations may be commenced.
USA C. J. Helder well Ho. 14, 1958, 8-5/8" easing was on econot for 24 hours, cas pressure for thirty minutes may be seen that this plan of work must receive mpany Pan American Petrole dress Box 487	I was specified on February 15, 1958, and on February 15 and on February 15, 1958, and on February 15 and all 495 with 460 sacks of count. After uniting and water shut-eff were tested with 500 pounds which held with no drop in pressures. FEB 21 1958 OIL CON 32 ORIGINAL 324 ORIGINAL 324 ORIGINAL 324