
Form 9-331 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa	Fe	_
Lease No.	078904	·	
Gal	legge	Canmon	IIn4

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENTSUPPLEMENTARY WELL HISTORY

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 83 is located 990 ft. from In line and 990 ft. from In line of sec. 26 NE/4 Section 26 T-28-N R-12-W N.M.P.M. (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Wildcat San Juan New Mexico	Gallegos Canyon Unit		Farmington	, New Mexico	November 28, 19 58
(½ Sec. and Sec. No.) (Twp.) (Range) (Meridian) Wildest San Juan New Mexico	Well No. 83 is located	990 ft. from	m_{-} line and	990 ft. from	E line of sec. 26
(½ Sec. and Sec. No.) (Twp.) (Range) (Meridian) Wildcat San Juan New Mexico	NE/A Section 26	T-28-N	R-12-W	N.M.P.M.	
W11GG4 COLL COLL COLL COLL COLL COLL COLL COL	(½ Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)	
	Wildcat				
(Field) (County or Subdivision) (State or Territory)	(Field)	(County	or Subdivision)	(State	e or Territory)

The elevation of the derrick floor above sea level is 5817 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Gallegos Canyon Unit Well No. 83 was spudded on November 22, 1958, and on November 23, 1958, 9-5/8" casing was set at 523' with 500 sacks neat cement. After waiting on cement, casing and water shut off were tested to 800 pounds pressure for thirty minutes, which held with no drop in pressure. Reduced hole to 8-3/4" at 523' and resumed drilling operations.

Title Field Clerk