(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	
Lease No.	_NM_020501
Unit	

I C. STANTINGE TO DIVIEL		SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANG	E PLANS	
NOTICE OF INTENTION TO TEST V	NATER SHUT-OFF	
NOTICE OF INTENTION TO RE-DR	ILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT	OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL (OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABAND	OON WELL	
Oil String	()	
(INDI	ICATE ABOVE BY CHECK MARK N	ATURE OF REPORT, NOTICE, OR OTHER DATA)
		July 5, 19 57
Ohio Govt. Sec. 26	•	· · · · · · · · · · · · · · · · · · ·
	located 790 ft from	$\{\begin{array}{c} N \\ S \end{array}\}$ line and 1850 ft. from $\{\begin{array}{c} E \\ W \end{array}\}$ line of sec. 26
7 CH 1 10	located	S me and 1332 me of sec. 129
NW Sec. 26. (M Sec. and Sec. No.)	28 N	11 W (Range) (Meridian)
Kutz Canyon	San Juan	New Mexico
(Field)	(County or	Subdivision) (State or Territory)
		S OF WORK
	ing points, and all oth	, weights, and lengths of proposed casings; indicate mudding Jobs, cement- er important proposed work)
n 50 jts., 166 3.33' th 550 sacks cement rculated cement to s	net of 5-1/2", 15 2% jel, bumped pl surface shut off w	, weights, and lengths of proposed casings; indicate mudding lobe, coment-
n 50 jts., 1663.33' th 550 sacks cement roulated cement to s 3-57. Top cement by	net of 5-1/2", 15 2% jel, bumped pl surface shut off w Temp. survey 35'	weights, and lengths of proposed casings; indicate mudding Jobs, comenter important proposed work) .5#, J-55 casing, landed 1660 KB, cemented ug with 1200#, displaced with 39 bbls. ater and gas flow. Plug down 12:00 pm below surface pipe.
n 50 jts., 1663.33' th 550 sacks cement roulated cement to s 3-57. Top cement by	net of 5-1/2", 15 2% jel, bumped pl surface shut off w y Temp. survey 35'	weights, and lengths of proposed casings; indicate mudding Jobs, comenter important proposed work) .5#, J-55 casing, landed 1660 KB, cemented ug with 1200#, displaced with 39 bbls. ater and gas flow. Plug down 12:00 pm below surface pipe.
n 50 jts., 1663.33' th 550 sacks cement reulated cement to s 3-57. Top cement by Copy to New Mexico O	net of 5-1/2", 15 2% jel, bumped pl surface shut off w Temp. survey 35' il Conservation Cook must receive approval in w	weights, and lengths of proposed casings; indicate mudding Jobs, comenter important proposed work) .5#, J-55 casing, landed 1660 KB, cemented ug with 1200#, displaced with 39 bbls. ater and gas flow. Plug down 12:00 pm below surface pipe.
th 550 sacks cement reulated cement to s 3-57. Top cement by Copy to New Mexico Of understand that this plan of we company The Ohio Address P.O. Box	net of 5-1/2", 15 2% jel, bumped pl surface shut off w Temp. survey 35' il Conservation Cook must receive approval in w	weights, and lengths of proposed casings; indicate mudding Jobs, comenter important proposed work) .5#, J-55 casing, landed 1660 KB, cemented ug with 1200#, displaced with 39 bbls. ater and gas flow. Plug down 12:00 pm below surface pipe.