

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122
Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool San Juan Formation San Juan County San Juan
Initial I Annual _____ Special _____ Date of Test May 4, 1964
Company San American Petroleum Corp. Lease Williams Canyon Unit-Sub. Well No. 155
Unit I Sec. 23 Twp. 23-N Rge. 12-W Purchaser _____
Casing 4-1/2" Wt. 18.30 I.D. 4.022 Set at 6470' Perf. 6312-27' To 6320-24'
Tubing 2-3/8" Wt. 4.70 I.D. 1.973 Set at 6312' Perf. Open To Bottom
Gas Pay: From 6312' To 6320' L 6315' xG .700 -GL 4440' Bar.Press. 12
Producing Thru: Casing _____ Tubing I Type Well Single
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: April 27, 1964 Packer None Reservoir Temp. _____

OBSERVED DATA

Tested Through (PROVOST) (Choke) (PROVOST) Type Taps Flange

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Line) Size	(Choke) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI	7 days					1500		1500		
1.	1 day	.750	200			200	60° sat.	200	60° sat.	1 hour
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wPf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12,300		210	1.000	.9230	1.027	2400
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})
Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2010 P_c² 4,040,100

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w /P _c
1.						402,004	3,647,296		
2.									
3.									
4.									
5.									

Absolute Potential: 4,057 MCFPD: n .73
COMPANY San American Petroleum Corporation
ADDRESS Box 400, Farmington, New Mexico
AGENT AND TITLE Fred L. Moore, District Engineer
WITNESSED By:
COMPANY _____

ORIGINAL SIGNED BY
F. W. Foell
REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .