Pool Angel Peak

Tubing 2-3/8 Wt. 4.6

Producing Thru: Casing__

(Prover)

(Line)

Size

No.

Company Redfern & Herd, Inc.

Initial

Casing 4

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Formation Dakota

Sec. 22 Twp 288 Rge. 118 Purchaser_

Wt.9.5 & I.D. Set at 6318 Perf. 6090

___Tubing ___

Diff.

 $h_{\underline{\boldsymbol{W}}}$

Lease_ Chio

_I.D.____Set at 6194 Perf. 6191

Temp.

 \circ_{F} .

OBSERVED DATA

Tubing Data

Press.

psig

2124

_____Annual______Special__

Gas Pay: From 6090 To 6272 L xG .700 _GL

Date of Completion: 4-7-60 Packer

Flow Data

Press.

psig

Tested Through (Trover) (Choke) (Meter)

(Choke)

Size

(Orifice)

TION COMMISSION														
Form C-122														
TEST FOR GAS WELLS Revised 12-1-55														
			c	county	Sen J	uan.								
			_E	ate of '	Test_4	-21-	-60							
)				Wel:	l No	/1								
Pu	Purchaser													
	Per	rf. 6090)		то 6272									
		rf. 6191												
_														
	Type Well Single - Cas													
Single-Bradenhead-G. G. or G.O. Dual														
Reservoir Temp.														
ATA														
Type Taps														
		Data				∓	Duration							
			Press.				of Flow							
sig		°F.	psig		³F∙	╁	Hr.							
						士								
				1301		+-	3 hrs							
_						‡_								
						1								
ľ	ONS	Gravity		Compre	SS.	Rat	e of Flow							
		Factor		Factor		Q-	Q-MCFPD							
		Fg		Fpv		@ 1	.5.025 psia							
1														
\Box		.9258	_	1,06	5	6	706							
Α'.	ric	ONS												
		Speci	fi	c Gravit	су Ѕер	arat	or Gas							
		Speci Pc-	ſį	c Gravit 6	rg Flo	wing 562	Fluid							
		^ C			U									
	B 0			$P_c^2 - P_w^2$	T		D							
)		P _w 2		r _c -r _w		al. P _w	Pw Pc							
_		1724	4	638	ļ		1.610							
	_													
_		3 40												

 -		3/4	544		72		1301		3 APS			
				,	₽Т∩₩ ₽ <u>₩</u> Т₽Ĭ∏ ₩₽Т	ONS						
Cos	FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow											
,	-111010	_		110000	Factor	Factor	Factor		Q-MCFPD			
(24-Hour)) _/	h _w p _f	psia	F_{t}	Fg	Fpv	@ 1	@ 15.025 psi			
			" -									
	-4-						1 200	-				
12.365				596	.9667	.9258	1.066	67	6706			
L						L						
				PR'	ESSURE CALCULA	TIONS						
		arbon Ra	tio		cf/bbl.	Speci	fic Gravity	Separat	or Gas			
vity of Liquid Hydrocarbons_ (1-e			rbons		deg.	Speci	Specific Gravity Separator das					
			_(1-e_2			Pc		ĉ				
$P_{\mathbf{w}}$						1						
		$P_{\mathbf{t}}^2$	$F_{\mathbf{c}}^{\mathbf{Q}}$	$(F_cQ)^2$		P _w 2	$P_c^2 - P_w^2$	Cal.	Pw Pc			
Pt (I	psia)				(1-e ^{-s})			P _{w_}	Pc			
				<u> </u>								
1919						1724	2638		1,610			
				 								
olutel	Potenti K edi	959	2		MCFPD; n ⁷⁵	1.43						
PANY	Kedi	ern a tie	rd Ine.									
~~~ <del>~~</del>	<b>30</b> %	1747, H1	Glenc,	Teams	5							
			gas, v	meulting	with the At							
NESSED PANY	<del></del>											
TANI					REMARKS	<del></del>		OFP ET				
					1001 1111110			PLUL!	A			
							Ι Λ	AMIL -	(0)			
							lou	SAY1 1 19	)Co			
					•		1 SIL	CON 13	<b>0</b> ()			
								CON CONST. 3				
								· ' ' ' '				
									-			

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure  $(P_w)$ . MCF/da. @ 15.025 psia and 60° F.
- $P_c$ 2 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- $P_{w}$  Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- $F_{t}$  Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\rm W}$  cannot be taken because of manner of completion or condition of well, then  $P_{\rm W}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\rm t}$ .