


(SUBMIT IN TRIPLICATE)

Indian Agency Navajo



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Allottee \_\_\_\_\_

Contract No. 14-20-603-2206

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

AMARILLO-NAVAJO

December 3, 1961

Well No. 2 is located 660 ft. from N line and 660 ft. from E line of sec. 22

NE/4 NE/4 Section 22 2d North 14 West NMPM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5689 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is proposed to plug and abandon the above well as follows: Set cement retainer on top of Gallup and squeeze perforations at 5140' to 5160'. If 5-1/2" casing stub is above 2000', then place 100' cement plug 50' in and 50' out of stub. Place plug at top of surface casing and set up dry hole marker.

CONFIRMING MR. KRAHL TO MR. MORRILL DECEMBER 6, 1961.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Gulf Oil Corporation

Address P. O. Box 1971

Casper, Wyoming

By \_\_\_\_\_

cc: New Mexico O&G Cons. Comm. (2)

Title Area Engineer

*[Faint, illegible text, possibly bleed-through from the reverse side of the page]*

