

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **077976-A**
Unit **Jones "A"**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 7th, 1960

Well No. 1 is located 660 ft. from [S] line and 1980 ft. from [E] line of sec. 17
SE 1/4 SW 1/4 Sec. 17 28N 13W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)


The elevation of the derrick floor above sea level is 5992 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-19-60 TD 5700' RKB. Set 176 joints 5690' of 4-1/2" OD 9.5# J-55 casing at 5699' with 200 sacks regular cement, 25# Gilsontite per sack and 1/2# floccle per sack. Temperature survey showed top of cement at 4610'.

5-25-60 Pressured up on casing to 1000#. No pressure decrease in 1 hour.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company HENSON-MONTIN-GREER DRILLING CORP.

Address 158 Petroleum Center Building
Farmington, New Mexico

By _____

Title Vice-President