يتعرو وأوليون

Form Approved.

## UNITED STATES

	Budget Bu	reau No. 42R142
LEASE	- 1 - 1	

DEPARTMENT OF THE INTERIOR	SF-078	8106	<u> </u>	
GEOLOGICAL SURVEY	6. IF INDIA	N, ALLOTTEE O	R TRIBE NAME	
	/.us	<u> </u>		
SUNDRY NOTICES AND REPORTS ON WELLS		REEMENT NAM		01:55
(Do not use this form for proposals to drill or to deapen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	1 <del></del>		nit - Pictured	CILIT
	*8:" FARM U	R LEASE NAME		
1. oil gas well other	, 9. WELL NO	0		
2. NAME OF OPERATOR	V	131	7 7 7	
Energy Reserves Group, Inc.	10. FIELD O	R WILDCAT NA		
3. ADDRESS OF OPERATOR	West I	Kutz - Pic	tured Cliffs	
P.O. Box 3280 - Casper, Wyoming 82602		, R., M., OR BLI	K. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	17 TON D1	3 ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (	
below.) AT SURFACE: 660' FNL & 780' FWL (SE NW NW)		17-T28N-R1 OR PARISH 1		
AT TOP PROD. INTERVAL:		ian N		
AT TOTAL DEPTH:	14. API NO.		CW HCATCO	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		######################################		
REPORT, OR OTHER DATA	15. ELEVATI	ONS (SHOW D	F, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	GRD 5	,792 °	<u> z                                   </u>	
TEST WATER SHUT-OFF				
FRACTURE TREAT	1 1			
SHOOT OR ACIDIZE	1			
REPAIR WELL		rt results of multi ge on Form 9–330	ple completion or zone	
MULTIPLE COMPLETE		4 7 9 3		
CHANGE ZONES	± .			
ABANDON* U X				
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di</li> </ol>	e all pertinent	details, and gi	ve pertinent dates,	
measured and true vertical depths for all markers and zones pertinen	t to this work.)	* 3 5 7 7	Trace locations and	
Energy Reserves Group completed the following	procedure	e to plug	and abandon	
this well on 5-31-80.				
		1 等 4 等 4 3 章 3 数 3	3 × 3	
1. With tbg. in the well, loaded hole w/dril				
2. Spotted 10 sx Class "B" cement w2% CaCl	from 1,200	0' - 1,100	<b>'•</b>	
3. Spotted 10 sx Class "B" cement w2% CaCl <sup>2</sup> 4. Spotted 5 sx Class "B" cement w2% CaCl <sup>2</sup>	from 320'	220'.		
4. Spotted 5 sx Class "B" cement w2% CaCl <sup>2</sup> 5. Installed dry hole marker.	110111 30 -	- surrace.		
J. Installed dry note marker.				
Clean up and restoring of the location is pla	nned for t	the near f	uture.	
			78 3748	
		ាស្តីស្តីស្តី របស់ស្តីស្តីស	높음 중요에요 기름 중요	
Subsurface Safety Valve: Manu. and Type				
Subsurface Safety valve: Maffu. and Type		Set @	Ft.	
18. I hereby certify that the foregoing is true and correct				. 8
SIGNED Bolly Patrick TITLE Production En	gr-RMD	June	3, 1980	U
(This space for Federal or State office		CF N.	PKUYL	_
APPROVED BYTITLETOTALL CONDITIONS OF APPROVAL, IF ANY:	DATE	(200 3 K)	CHARACTER OF THE PARTY OF THE P	ş.
		tage of the second	Section 1970	H <sup>*</sup>
to the off		# 10 P P P P P P P P P P P P P P P P P P	SE VEIETNAN	:0
Section 3.		유 <u>취 중</u> 3	M. MIELLINAGE	714