I

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Offic	• \$	ani	a Fe	-
Lease No.	SF	.07	7944	
Unit	C.	J.	Holder	_

	NOTICES	AND	<b>REPORTS</b>	ON	WELLS
CHINDRY	NOTICES.	AND	KELOKIS	OII	

OTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
TICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOUTING OR ACIDIZING
TICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALIERING CASING
TICE OF INTENTION TO RE-DRILL OR REPAIR WE	SUBSEQUENT REPORT OF RE-DRILLING OR REFAIL
TICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
OTICE OF INTENTION TO PULL OR ALTER CASING	
TICE OF INTENTION TO ABANDON WELL	
	CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
J. Holder	Farmington, New Mexico December 5 , 19
	ft. from S line and sio ft. from E line of sec.
l No. 3 is located	S me and
J. and annetes # Tu The	- R-13-V N. F. P. M. M. P. M.
(1/2 Sec. and Sec. No.) (Twp	.) (Range) (Meridian)
	(County or Subdivision) (State or Territory)
to names of and expected depths to objective sa	DETAILS OF WORK  nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cer
pudded 12-1/4" hole on Dece asing at 202" with 200 sack rulated 25 sacks of sement.	mds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereints, and all other important proposed work)  mber 1, 1960, and drilled to 202'. Set 8-5/8"  is coment containing 15 calcium chloride. Cir-  ifler waiting on coment, tosted casing with  the bold with no indication of pressure drop.
pudded 12-1/4" hole on Dece lasing at 202" with 200 sack rulated 25 sacks of sement.	mds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereints, and all other important proposed work)  mber 1, 1960, and drilled to 202'. Set 8-5/8"  is coment containing 15 calcium chloride. Cir-  ifler waiting on coment, tosted casing with  the bold with no indication of pressure drop.
pudded 12-1/4" hole on Dece lasing at 202' with 200 sack rulated 25 sacks of community	mos; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereints, and all other important proposed work)  mber 1, 1960, and drilled to 202'. Set 6-5/8"  is coment containing 15 calcium chloride. Cir-
padded 12-1/4" hole on Dece pasing at 202" with 200 sack rulated 25 sacks of cement. 1000 pcd for 30 minutes which Reduced hole to 7-7/8" at 20	mos; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereints, and all other important proposed work)  mber 1, 1960, and drilled to 202'. Set 8-5/8* is coment containing if calcium chloride. Cir- ifler waiting on coment, tested easing with the held with no indication of pressure drop.  2' and resumed drilling operations.  DEC 8 1960  OIL CUN CUM DIST. 3
padded 12-1/4" hole on December 2021 with 200 sack rulated 25 sacks of commt. 1000 pcd for 30 minutes which deduced hole to 7-7/8" at 20	mos; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certifies, and all other important proposed work)  mber 1, 1960, and drilled to 202. Set 8-5/8* is coment containing if calcium chloride. Cir- ifler waiting on coment, tosted sasing with the held with no indication of pressure drop.  2 and resumed drilling operations.  DEC 8 1960  OIL CUM. CUM. DIST. 3  ive approval in writing by the Geological Survey before operations may be ommenced.
padded 12-1/4" hole on Dece asing at 202" with 200 sack nulated 25 sacks of commt. .000 pci for 30 minutes which leduced hole to 7-7/8" at 20	nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereints, and all other important proposed work)  mber 1, 1960, and drilled to 202. Set 8-5/8*  is coment containing if calcium chloride. Cir-  after waiting on coment, tested sasing with  the lid with no indication of pressure drop.  2' and resumed drilling operations.  DEC 8 1960  OIL CUN. CUM.  DIST. 3  ive approval in writing by the Geological Survey before operations may be ommenced.
pudded 12-1/4" hole on Dece lasing at 202" with 200 sack rulated 25 sacks of sement. 1000 pcd for 30 minutes which leduced hole to 7-7/8" at 20	nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereints, and all other important proposed work)  mber 1, 1960, and drilled to 202. Set 8-5/8*  is coment containing if calcium chloride. Cir-  ifler waiting on coment, tosted sasing with the held with no indication of pressure drop.  2' and resumed drilling operations.  ORC 8 1960  OIL CUN CUM DIST. 3  ive approval in writing by the Geological Survey before operations may be ommenced.  R. M. Beller, in.
pudded 12-1/4" hole on Dece asing at 202" with 200 sack ulated, 25 sacks of coment. 000 pai for 30 minutes which deduced hole to 7-7/8" at 20 1 understand that this plan of work must receive company Pan American Petro	nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereints, and all other important proposed work)  mber 1, 1960, and drilled to 292. Set 6-5/88  is coment containing 18 calcium chloride. Cir-  after waiting on coment, tested casing with the held with no indication of pressure drop.  2. and remained drilling operations.  OIL CUN. CUM. DIST. 3  ive approval in writing by the Geological Survey before operations may be emmenced.  R. M. Belle, it.
modered 12-1/L* hole on December 12-1/L* hole of cement.  100 per for 30 minutes which duced hole to 7-7/8* at 20 minutes which hole to 7-7/8* at 20 minutes which hole to 7-7/8* at 20 minutes which hole to 7-7/8* at 20 minutes hole to	mas; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centre, and all other important proposed work)  mber 1, 1960, and drilled to 292. Set 6-5/88  is coment containing 15 calcium chloride. Cir-  if or waiting on coment, tested casing with  the held with no indication of pressure drop.  2' and remined drilling operations.  DEC 8 1960  OIL CUN. CUM. DIST. 3  ive approval in writing by the Geological Survey before operations may be ommenced.  R. M. Ballet, it.