

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		3. WELL NO. 8	
2. NAME OF OPERATOR HICKS OIL & GAS, INC.		7. UNIT AGREEMENT NAME Southeast Cha Cha	
3. ADDRESS OF OPERATOR P.O. Drawer 3307- Farmington, NM 87499		8. FARM OR LEASE NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 680' FSL & 810' FEL		10. FIELD AND POOL, OR WILDCAT Cha Cha Gallup	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 8, T28N, R13W	
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 6034' KB		12. COUNTY OR PARISH San Juan	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

12/06/88

- 1) Spotted 51 sx Class B Cement from 5710' to 5270'. Gallup Top 5320'. Spotted mud from 5270' - 3230'.
- 2) Perforated @3230'. Set cement retainer @2560' and spotted 361 sx Class B Cement from 3230' - 2510' inside and outside casing. (Mesa verde Top 3180', Chacra Top 2560'). Spotted mud from 2510' - 1700'.
- 3) Perforated @1700'. Set cement retainer @1320' and spotted 216 sx Class B Cement from 1700' - 1270' inside and outside casing. (Pictured Clif Top 1650', Fruitland Top 1320'). Spotted mud from 1270' - 400'.

12/07/88

- 4) Perforated @400'. Pumped 200 sx Class B Cement and circulated cement to surface.
- 5) Erected dry hole marker.

Approved by \_\_\_\_\_  
Special Agent in Charge  
Bureau of Land Management  
U.S. Department of the Interior

18. I hereby certify that the foregoing is true and correct

SIGNED

JIM HICKS

TITLE - PRESIDENT

DATE 12/09/88

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE 12/15/88

James E. Edwards Jr.  
Special Agent in Charge  
Bureau of Land Management  
U.S. Department of the Interior

\*See Instructions on Reverse Side

NMOCC