

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

NMSF-080844-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Gallegos Canyon Unit

254

9. API Well No.

3004511801

10. Field and Pool, or Exploratory Area

Pinon Gallup

11. County or Parish, State

San Juan

New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Patty Haeefe

3. Address and Telephone No.

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL

720' FEL

Sec. 19 T 28N R 11W

Unit I

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Amoco Production Company has plugged and abandoned this well per the following:

MIRUSU 12/23/95. Set retainer at 5390', test casing to 500 psi, held. Test tubing to 1000 psi, held. Squeeze 5648-5648' with 87 sx Class B 65/35 poz, 14.0 ppg. Plugback 5648-4247' with 87 sx cement. Squeeze 3800-645' with 183 sx Class B 65/35 poz, 14.0 ppg. Plugback 3800-645 with 183 sx cement. Squeeze 645-surface with 80 sx Class B neat, 15.6 ppg. Plugback 645-surface with 50 sx Class B neat. Cut off wellhead and fill surface casing with 30 sx Class B neat cement to surface. Install P&A marker.
RDMOSU 12/29/95.

RECEIVED
BLM MAIL ROOM
96 JAN 16 PM 3:49
BUREAU OF LAND MANAGEMENT, NM

14. I hereby certify that the foregoing is true and correct

Signed

Patty Haeefe

Title

Staff Assistant

Date

01-11-1996

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.