

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-078863

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Krause

9. WELL NO.

61

10. FIELD AND POOL, OR WILDCAT

Kutz P.C. West

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28-T28N-R11W
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
R&G DRILLING CO.

3. ADDRESS OF OPERATOR
c/o Walsh Engineering & Production Corp.
P.O. Box 254, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1490' FSL, 1815' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5781' GR, 5791' DF, 5792' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-19-76

Spud Well

Ran 2 jts, 8-5/8", 24.0 lb, K-55 casing (90.80').

Set at 102.80' with 100 sacks Class "B" cement with 2% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Test with 500 psig. Test O.K.

12-22-76 T. D. 1861'

Ran 45 jts. 4-1/2", 10.50# & 11.60#, ST&C & LT&C, casing (1800.35')
Set at 1810.35' with 125 sacks Halliburton "Light" cement, 12% gel, following by 125 sacks 50/50 Pozmix "A" with 6-1/4 lbs Gilsonite per sack and 6 lbs salt per sack. Cement circulated.

RECEIVED

FEB 14 1977

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

For: R&G Drilling Co.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ewell N. Walsh, P. E.

President, Walsh Engineering &

Production Corp.

DATE Feb. 11, 1977

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side