

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

6. LEASE DESIGNATION AND SERIAL NO.

SF-078863

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Krause

9. WELL NO.

61

10. FIELD AND POOL, OR WILDCAT

Kutz Fruitland Ext.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28-T28N-R11W

N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

R&G Drilling Company

3. ADDRESS OF OPERATOR

c/o Walsh Engr. & Prod. PO Box 254, Farmington, NM 87401
Corp.4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1490' FSL, 1815' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5781' GL, 5792' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

2-11-77

Set temporary bridge plug at 1630' to test Fruitland formation.

2-18-77 PBTD 1630'

Sandwater frac perforations 1468'-1552'.

Pad	-3,170 gals
Water	-25,100 gals
Sand	-25,000 lbs.
Flush	- 1,200 gals
Breakdown	-None
Max. Treat Press.	- 1,800 psig
Ave. Treat Press.	- 1,600 psig
Ave. Inject. Rate	- 39 BPM
Instantaneous SIP	- 1,000 psig
5 minute SIP	- 850 psig
15 minute SIP	- 800 psig



APR 14 1977

For: R&G Drilling Company

18. I hereby certify that the foregoing is true and correct

SIGNED

Ewell N. Walsh, P.E.

TITLE

President, Walsh
Engr. & Prod. Corp.

DATE April 13, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side