(Other)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

Form approved Budget Bureau No. 42 R1424 5 LEASE DESIGNATION AND BERTAL NO.

GEOLOGICAL SURVEY

SF-078673

	.					-	
SUNDRY NOTICES AND REPORTS ON WELLS	6	, IF	INDIAN.	ALLOTTEE	, ur ·	TRIBL	NANE.

the not use this form for proposi-	CES AND REPORTS (has to drill or to deepen or plug TION FOR PERMIT" for such p	pack to a different reservoir.				
OIL GAS WELL OTHER			7. UNIT AUREEMENT NAME			
2. NAME OF OPERATOR			8. FARM OR LEASE NAME			
R & G DRILLING	Schlosser					
	sh Engineering &		9. WELL NO.			
4. Location of WELL (Report location of See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT Kutz Fruitland					
910'FSL, 1060	'FWL		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27-T28N-R11W			
14. PERMIT NO.	15. ELEVATIONS (Show whether Di	r, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE			
	5780'GR, 5790'D	F, 5791'KB	San Juan NM			
16. Check Ap	propriate Box To Indicate N	Nature of Notice, Report, or (Other Data			
NOTICE OF INTEN	rion to:	SUBSEQ	ENT REPORT OF:			
TEST WATER SHOT OFF	CULL OR ALTER CASING	WATER SHUT-OFF FRACTURE TREATMENT	REPAIRING WELL ALTEBING CASING			
SHOOT OR ACIDIZE	BANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*			
DEDLID WITH	HANCE PLANS	(Other)				

- (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - Spud well. 12-27-77

CONDITIONS OF APPROVAL, IF ANY:

Ran 3 jts. $8 \frac{5}{8}$ ", 24.0 lb., K-55 casing (93). Set at 104' with 100 sacks Class "B" cement with 3% CaCl and 4 lb. Flocele per sack. Cement circulated. Test with 500 psiq. Test OK.

T.D. 1725' Ran 41 jts., $4\frac{1}{2}$ ", 10.50 lb., K-55 casing 11-30-77 (1675'). Set at 1686' with 250 sacks, 65/35 Pozmix with 12% gel and $6\frac{1}{4}$ lbs. Gilsonite per sack, 100 sacks 50/50 Pozmix "A" with $6\frac{1}{4}$ lb. Gilsonite per sack. Cement circulated.

FOR: R & G Drilling Co.		The state of the s
18. I hereby certify that the torogoing is true and out ect	President, Walsh Engineer	ing &
STONE EWELL N. Walsh P. F.	TITLE Production Corporation	DATE February 3, 1978
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE