

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R/424.
5. LEASE DESIGNATION AND SERIAL NO.

SF-078863

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

R & G Drilling Company

3. ADDRESS OF OPERATOR

c/o Walsh Engr., P.O. Box 254, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1190'FSL, 1125'FEL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Krause

9. WELL NO.

64

10. FIELD AND POOL, OR WILDCAT

Kutz Farmington

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 29-R28N-R11W

N.M.P.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5789'GR, 5799'DF, 5800'KB

12. COUNTY OR PARISH

San Juan

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-7-78 Set temporary bridge plug as 1280'.

5-8-78 See Sandwater Fracture Treatment - Attached

For: R & G Drilling Company

18. I hereby certify that the foregoing is true and correct

SIGNED

Ewell N. Walsh, P.E.

TITLE

President, Walsh Engr.
& Production Corp.

DATE

6-6-78

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

R & G DRILLING COMPANY
Krause No. 64
Lease No. SF-078863

Temporary Bridge Plug		1280'	
Perforations:		900'-905', 917'-928', 1051'-	
		1056', & 1136'-1142' (Farmington)	
Sandwater Fracture:			
Pad	1000	gallons	
Water	14,000	gallons	
Sand	20,000	lbs.	
Flush	1,500	gallons	
Breakdown Press.	None	psig.	Pump in 1500 psig
Ave. Treating Press.	1,650	psig.	
Max Treating Press.	1,750	psig.	
Ave. Injection Rate	40.0	BPM	
Hydraulic Horsepower	1,618	HHP	
Instantaneous SIP	450	psig.	
5 Minute SIP	450	psig.	
10 Minute SIP	425	psig.	
15 Minute SIP	400	psig.	