

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
Energy Reserves Group, Inc.  
3. ADDRESS OF OPERATOR  
P. O. Box 3280 Casper, Wyoming 82602  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1700' FSL & 1590' FEL (NW SE)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Well History			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The above described well was spudded @ 4:30 p.m., 8-29-79.  
Drld 12 1/4" hole to 128'.

Ran 3 jts 8 5/8" O.D. 36#, K-55, 8Rth, R-3, New csg set @ 127' (K.B.) cemented w/110 sx of Class "B" cement w/2% CaCl<sub>2</sub> & 1/4# Flocele/sx. Plug down @ 4:30 a.m., 8-31-79. Good cement returns. Pressured tested BOPE to 800 PSI, held O.K.

Drilled 6 3/4" hole to 1530' & ran logs.

Ran 38 jts 4 1/2" O.D. 10.79# 8Rth, R-3 ST&C, New csg set @ 1629' (K.B.) Cemented w/50 sx of pozmix w/12% gel & 1/4" Flocele followed by 175 sx of Class "B" cement w/ 1/4# Flocele/sx, good cement returns.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Drlg. Supt. DATE 9-5-79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: