ويافي وحدد

3 H 3 7 H 6

5. LEASE

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

DEPARTMENT OF THE INTERIOR	SF-078019
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas well to other	E.H. Pipkin
well well other  2. NAME OF OPERATOR	9. WELL NO.
	9-E
Energy Reserves Group, Inc. 3. ADDRESS OF OPERATOR P.O. Box 3280, Casper, Wyoming 82602	10. FIELD OR WILDCAT NAME Basin - Dakota
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA
AT SURFACE: 940' FNL & 950' FWL (NW/NW)	Sec. 35-T28N-R11W 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan ARRISH 13. STATE
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	<u> </u>
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	G.L. 5,748' KB 5,758'
TEST WATER SHUT-OFF [] [X]	
FRACTURE TREAT  SHOOT OR ACIDIZE	1 H D 48 18 - 28 13 -
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING  MULTIPLE COMPLETE  MULTIPLE  MULTIPLE COMPLETE  MULTIPLE  M	Change on Form 9–330.)
CHANGE ZONES	
ABANDON*	,, 29년에 전했다. 경우대리 그로 송흥대중 모양
(other) Well History X	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (etearly state including estimated date of starting any proposed work. If well is directly measured and true vertical depths for all markers and zones pertinent. The above referenced well was spudded @ 5:30 . Drilled 12-1/4" hole to 690". Ran 17 jts. 8-5 ST&Cm new casing set @ 685" (K.B.) Cemented to Celloflake per sx. Plug down @ 10:00 AM 12-19.	AM 12-17-79. /8" O.D. 24# K-55 8Rth, R-3, SS, w/475 sx Class "B" cement w/1/4# -79. Good cement returns
Nipple up and pressure tested BOPE to 800 psi	- held o.k.
12-21-79: Drilled 7-7/8" hole @ 875'.	
	18 3 mg
	JANA DE BATTA DE PRIMA DE
No.	
Subsurface Safety Valve: Manu. and Type	Set @Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED TITLE Drilling Forem	an pare 12-27-79
(This space for Federal or State office	
	e use)
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
	74 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
ner de na	25 M2
	े मार्गिक्षणा की वार्ति हैं।
*See Instructions on Reverse Sid	EY,